

PROJECT:			
ITEM #		OTY:	
MODEL #			
. 10522 11	010 "		
AIA #	SIS #		_

WORKTOP REFRIGERATOR WITH DRAWERS

VWRD72HC-6



EXCLUSIVE WARRANTY

- 7 Year Parts, Labor and Compressor
- Exclusive 2 Year Warranty On Magnetic Door Gaskets
- ► Lifetime Warranty On Handles & Hinges (parts only)





CABINET CONSTRUCTION

- · Stainless Steel Exterior (galvanized back & bottom)
- · Aluminum Interior
- · 20 Gauge Stainless Steel Drawers
- · 4" High, Foamed-In-Place Backsplash
- · One Piece, Snap-In Magnetic Drawer Gaskets
- · 6" Casters Two With Brakes
- 8' Cord And Plug (see electrical data for details)

FEATURES

- · Full Electronic Control
- · Stay-Open Drawer Feature For Easy Product Loading
- · Low Profile Horizontal Drawer Handles
- · Heavy-Duty Pan Supports Provided
- Drawers Accommodates 6" Deep Full Size Food Service Pans In Both Upper And Lower Drawers (pans not included)
- · Telescoping Drawer Slides With Locking Mechanism

REFRIGERATION

- Refrigeration System Uses R-290 Refrigerant To Comply With All Environmental Concerns
- Rear Mounted Refrigeration System
- Adaptive Defrost For Reduced Energy Consumption And More Consistent Product Temperatures
- · Epoxy Coated Evaporator Coil
- Refrigerator Capable Of Maintaining Product Temperature 36°F To 38°F



OPTIONS & ACCESSORIES

- · Stainless Steel Interior
- · Stainless Steel Back

· Cutting Board

- Drawer Locks
- 6" Legs Or 6" Seismic Legs
- Casters: 3", Roller Kit, Low Profile
- Remote Models* (6" legs only)
 (refrigerant must be specified at time of order,
 see note on back on page)

3779 Champion Blvd, Winston-Salem, NC 27105

ph: (888) 845-9800 fax: (800) 253-5168

Sales@VictoryRefrigeration.com VictoryRefrigeration.com


Rev. 7/18/24 Printed in U.S.A.


APPROVAL: _____ DATE: ____





VWRD72HC-6











We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM)

3" Bottom & 2" Rear clearance is required

CHARACTERISTICS ELECTRICA		ELECTRICAL DATA	AL DATA		SHIPPING DETAILS	
Net Capacity (cubic ft.)	17.88	Cabinet Voltage	115/60/1	Height	48"	
Width, Overall (in.)	72"	Total Amperes	3.0	Width	74"	
Depth, Overall (with handle)	32 5/8"	NEMA Plug (8' cord)	5-15P	Depth	38"	
Height Overall (6" casters)	39 5/8"	REFRIGERATION DATA		Crated Weight	438 lbs	
Depth, Drawer Open 90°	48 5/8"	Condensing Unit Size, HP	1/5	*NOTE: Remote units are field		
Drawer Opening (in.)	19 1/2" x 7 1/2" 19 1/2" x 11 1/8"	Refrigerant*	R-290			
No. Of Drawers	6	Capacity (BTU/HR) (100°F/20°F)	1350	wired and comes with 6" legs. Refrigerant must be specified at time of order.		
		Heat Rejection (BTU/HR)	2025			
		Charge (lbs/grams/ounces)	0.2646 / 120 / 4.24			

3779 Champion Blvd, Winston-Salem, NC 27105 | ph: (888) 845-9800 | fax: (800) 253-5168

Rev. 7/18/24 Printed in U.S.A.

