

Curved glass



Ambient assisted service - RMA

RMA

Optimax Patisserie units are available in hot ambient and chilled versions suitable for either assisted or self-service applications. They are perfectly suited for delis, coffee shops, convenience stores and all food-to-go outlets. Enclosed to the front Model No: RMA65E - 650mm unit Model No: RMA100E - 1000mm unit Model No: RMA130E - 1300mm unit Unit shown RMA100E with black plastic coated steel base fascia panels & optional castor cover

Specifications

Dimensions: Model ----- Top size ----- loading RMA65E - - - 650 x 750 x 1445mm high - -13W
RMA100E - - 1000 x 750 x 1445mm high - - 21W RMA130E - - 1300 x 750 x 1445mm high - - 28W

Connection 220V/240V 1 phase 50 Hz. Cable Units fitted with 2 metres of cable and 13 amp plug.

Construction Bright polished & satin finish stainless steel with toughened glass screens.

Choice of stainless steel coloured plastic coated steel or wood laminate base fascia panels.

Electrical

Features

Standard Features: The assisted service models feature a full height toughened curved glass screen to the front, open to the rear with an option of sliding glass doors

- Illuminated display via integral fluorescent lighting.
- Three height adjustable removable 8mm toughened glass shelves for flexibility of display.
- Option of fluorescent lighting under each shelf.
- Supplied on four low level castors.
- Stainless steel lined ambient cupboard to rear.
- Stainless steel base for ease of cleaning.

Extras:

- Under shelf lighting - Slimline fluorescent tubes under each glass shelf.
- Shelf edge ticket strips - that simply clip to the front of the glass shelves.
- Glass doors to rear of display area.
- Stainless steel doors to rear ambient cupboard.
- Castor covers - satin finish stainless steel covers

Downloads

- [AutoCAD Block RMA100E](#)
- [AutoCAD Block RMA130E](#)
- [AutoCAD Block RMA65E](#)
- [Brochure Pages - Optimax](#)
- [Operating Instructions](#)