



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CCP-2G GD LC C CI 230V 1N 50Hz

19097962

05/05/2023

EU Model shown – UK models have castors as standard

DENOMINATION:

Refrigerated counter with glass doors and locks - Concept 700 Gastronorm with 2 doors.

DESCRIPTION :

- Structure built with AISI-304 stainless steel
 - 50 mm, 40 kg/m³ injected polyurethane insulation.
 - Forced draught cooling system inside the room.
 - Copper piping and aluminium flaps evaporator.
 - Digital display for electronic and digital control of temperature and defrosting.
 - The controls are integrated in the front panel for a better protection against dirt. IPX5 compliant, the controls are protected against water splash and jets.
 - Easier loading and unloading thanks to its door self-closing and stay open features.
 - Removable and height adjustable plastic covered steel shelves for easy cleaning (GN1/1 size).
 - Equipment per door: 1 GN 1/1 grid and 2 sets of height adjustable tray slides.
 - Built-in drainage to get rid of waste liquids inside the unit.
 - Interior LED lighting (only for models with glass doors).
 - Embedded bottom and curved panels inside for easy cleaning and maintenance.
 - Height adjustable stainless steel legs.
 - 10 cm high splashback.
 - Working temperature: from 0 °C to +8 °C (refrigerators) and from -18 °C to -22 °C (freezers).
 - Tested in climatic class IV.
- Refrigerated counters with glass doors.
VISIBILITY: Double pane door and anodised aluminium frame with double vacuum chamber.

POSSIBLE OPTIONS :

- Stainless Backing
- Legs instead of castors
- Without splashback
- Door frame resistance
- Granite worktop
- Left group
- Without breastplate
- Without Countertop
- Panoramic aperture

STANDARD:


- Glass door
- Locks
- Castors
- UK plug

POSSIBLE ACCESSORIES :

- ACCESSORIES
- ACCESSORIES FOR REFRIGERATION
- GASTRONORM GRIDS

DIMENSIONS

| | | | |
|------------|----------------------|----------------|----------------------|
| X Width | 1342 mm | X Gross width | 1455 mm |
| Y Depth | 700 mm | Y Gross depth | 825 mm |
| Z Height | 850 mm | Z Gross height | 1000 mm |
| Net Weight | 111,0 kg | Gross Weight | 116,0 kg |
| Net volume | 0,798 m ³ | Gross volume | 1,200 m ³ |



ELECTRICITY TECHNICAL SPECIFICATIONS

| | |
|--------------------|-----------|
| Electric power | 0,205 kW |
| Amperage (A) | 0,96 A |
| Voltage | 230V - 1N |
| Electric frequency | 50Hz |

GAS TECHNICAL SPECIFICATIONS

| | |
|----------|--------|
| Gas type | R-600a |
|----------|--------|

COLD TECHNICAL SPECIFICATIONS

| | |
|---------------------------|-------------|
| Refrigeration power | 0,361 kW |
| Annual elec. consumption | 1240,80 kWh |
| Power consumption 24h | 3,40 kWh |
| Gross internal volume | 274 L |
| Climate class | 4 |
| Cooling gas load | 64,000 g |
| Clasif. Energy efficiency | C |
| Energy Efficiency Index | 23,93 % |

CONNECTIONS TECHNICAL SPECIFICATIONS

| | |
|--------------------------|----------|
| Single-phase 230V wiring | 2X1+T-2A |
|--------------------------|----------|

OTHERS

| | |
|---------------------|-------|
| Number of doors | 2 |
| Condensation system | Vent. |





Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CCP-2G GD LC C CI 230V 1N 50Hz

19097962

05/05/2023

EU Model shown – UK models have castors as standard

