




ELECTRIC SPACE SAVER FRYER FILTER SYSTEMS

IMPERIAL


IFSSP250E MODEL NUMBERS

IFSSP250E	IFSSP175E
IFSSP350E	IFSSP275E
IFSSP450E	IFSSP375E
IFSSP550E	IFSSP475E
IFSSP650E	IFSSP575E
IFSSP650E	IFSSP675E

- Add suffix "T" for Electronic Thermostat
- Add suffix "C" for Computer Controls
- Add suffix "DC" for Digital Touchscreen Controls
- Suffix "E" denotes Immersed Elements
- Suffix "EU" denotes Tilt-Up Elements



**Touch Screen
Digital Controls
Now Available**



**Hands-free
Filter Connection
System**

FILTER PACKAGE CHOICES

- Up to six fryers can be battered into one fryer/filter system.
- Available for 50 and 75 lb (27 and 41 Liters) oil capacity fryers.
- Available with Snap Action Thermostats, Electronic Thermostats or Computer Controls.

UNIQUE FILTER PAN DESIGN

- Filter pan is designed for maximum oil return
- Stainless steel construction is easy to clean and has a professional look.
- Positive-latching filter paper holder holds paper in place for optimal filtration.
- Quick disconnect connection offers quick and safe connection of the filtered oil back into the frypots.
- All oil drain and return lines are internally plumbed for convenience and safety.

ROLLER-PUMP

- 5.5 GPM pump with a 1/3 HP motor speeds up the filtering process.
- Can pump oil into a disposal vat up to 20 feet away.

EXTERIOR FEATURES

- Continuous cabinet provides a professional look.
- 5" (127 mm) deep continuous stainless steel front landing ledge.
- Stainless steel precision welded frypot
- Includes casters, joiner strips, filter starter kit and fryer tip brush

LOCATED UNDER FRYERS

- Filter location under fryers saves valuable space.
- Internally plumbed oil drain and return line.

IMPERIAL


1128 Sherborn Street | Corona, CA 92879 | 800.343.7790 | imperialrange.com | imperialsales@imperialrange.com

©2026 Imperial Commercial Cooking Equipment. Imperial reserves the right to change specifications at any time without prior notice and without any obligation for past or future



ELECTRIC

SPACE SAVER FRYER FILTER SYSTEMS



SPACE SAVER FRYER/FILTER SYSTEMS

MODEL	OIL CAPACITY	WIDTH	FRYERS	SHIP WEIGHT KG	SHIP WEIGHT LBS
IFSSP250E/EU	50 LBS. (41 L)	31"(787MM)	2	284	626
IFSSP350E/EU	50 LBS. (41 L)	46½"(1181MM)	3	389	856
IFSSP450E/EU	50 LBS. (41 L)	62"(1575MM)	4	495	1092
IFSSP550E/EU	50 LBS. (41 L)	77½"(1969MM)	5	655	1445
IFSSP650E/EU	50 LBS. (41 L)	93"(2362MM)	6	770	1698
IFSSP175E/EU	75 LBS. (51 L)	19½"(495MM)	1	171	376
IFSSP275E/EU	75 LBS. (51 L)	39"(911MM)	2	268	590
IFSSP375E/EU	75 LBS. (51 L)	58½"(1486MM)	3	390	860
IFSSP475E / EU	75 LBS. (51 L)	78"(1981MM)	4	513	1130
IFSSP575E / EU	75 LBS. (51 L)	97½"(2477MM)	5	635	1400
IFSSP675E / EU	75 LBS. (51 L)	117"(2972MM)	6	758	1670

MODEL	DIMENSIONS	CRATED DIMENSIONS
IFSCB250E / EU	31" W X 34" D X 44 1/8" H (787 MM X 864MM X 1121MM)	32½" W X 39" D X 49½" H (826MM X 991MM X 1257MM)
IFSCB350E / EU	46½" W X 34" D X 44 1/8" H (1181 MM X 864MM X 1121MM)	48" W X 39" D X 49½" H (1219 MM X 991MM X 1257MM)
IFSCB450E / EU	62" W X 34" D X 44 1/8" H (1575 MM X 864MM X 1121MM)	63½" W X 39" D X 49½" H (1613 MM X 991MM X 1257MM)
IFSCB550E / EU	77½" W X 34" D X 44 1/8" H (1969 MM X 864MM X 1121MM)	79" W X 39" D X 49½" H (2007 MM X 991MM X 1257MM)
IFSCB650E / EU	93" W X 34" D X 44 1/8" H (1969 MM X 864MM X 1121MM)	94½" W X 39" D X 49½" H (2400 MM X 991MM X 1257MM)
IFSCB175E / EU	19½" W X 39" D X 46½" H (495 MM X 991MM X 1181MM)	26" W X 41" D X 53½" H (660 MM X 1041MM X 1359MM)
IFSCB275E / EU	39" W X 40½" D X 44 1/8" H (911 MM X 1029MM X 1121MM)	40½" W X 43" D X 49½" H (1029 MM X 1092MM X 1257MM)
IFSCB375E / EU	58½" W X 40½" D X 44 1/8" H (1486 MM X 1029MM X 1121MM)	40½" W X 43" D X 49½" H (1524 MM X 1092MM X 1257MM)
IFSCB475E / EU	78" W X 40½" D X 44 1/8" H (1981 MM X 1029MM X 1121MM)	40½" W X 43" D X 49½" H (2019 MM X 1092MM X 1257MM)
IFSCB575E / EU	97½" W X 40½" D X 44 1/8" H (2477 MM X 1029MM X 1121MM)	40½" W X 43" D X 49½" H (2515 MM X 1092MM X 1257MM)

ELECTRICAL REQUIREMENT PER FRYER

MODEL	TOTAL KW'S	VOLTS	PHASE	HZ	AMPS
50 LB/E	15.9	208	3	60	45
50 LB/E	15.9	240	3	60	39
50 LB/E	15.9	480*	3	60	20
50 LB/EU	16.1	208	3	60	46
50 LB/EU	16.1	240	3	60	40
50 LB/EU	116.1	480*	3	60	20
75 LB/E	19.6	208	3	60	56
75 LB/E	19.6	240	3	60	48
75 LB/E	19.6	480*	3	60	24
75 LB/EU	19	208	3	60	55
75 LB/EU	19	240	3	60	47
75 LB/EU	19	480*	3	60	24

FILTER ELECTRICAL REQUIREMENT

VOLTAGE	PHASE	HZ	AMPS
115V	1	60	6.8

* For export only
6ft (1829 mm) power cord with 3 prong plug provided

OPTIONS AND ACCESSORIES

- Automatic basket lifts with computerized controls
- Manual controlled basket lifts
- Gas shut off valve, 3/4" N.P.T.
- Stainless steel tank cover
- Stainless steel side drain shelf
- Stainless steel side splash
- Manual timer
- Goofer Declogger Rod
- Sediment Scooper
- Filter paper 40# thickness, 20 microns, 100 sheets per box

CLEARANCE REQUIREMENTS

For use only on non-combustible floors with legs or casters. Provide 0" clearance from non-combustible surfaces and 6" (152 mm) from combustible surfaces.



MADE IN USA

IMPERIAL

1128 Sherborn Street, Corona, CA 92879 | 800.343.7790 | imperialrange.com | imperialsales@imperialrange.com

©2026 Imperial Commercial Cooking Equipment. Imperial reserves the right to change specifications at any time without prior notice and without any obligation for past or future equipment purchases. Visit www.imperialrange.com for specification updates.