

## Prostore 500 1 Door Digital Refrigerator, 470lt (0/+10 °C) - R290

ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_


**691344 (PS04R1FHC)**

 1-door prostore Refrigerator  
 470lt, 0/+10°C, AISI 304,  
 R290

### Short Form Specification

#### Item No.

Full door refrigerator constructed in 304 AISI stainless steel with external bottom panel in anti-corrosive material. Large digital display featuring humidity selection button (3 preset level), cabinet temperature display and setting and turbo frost cycle (to rapidly cool warm loads). HACCP-compliant control with alarms and history. Frost Watch Control to defrost only when required with automatic evaporation of defrost water. Optimized airflow provides even temperature distribution on all grids. Fitted with 65 mm-thick polyurethane insulating foam. Self-closing, on-site reversible door features microswitch to switch off the fan when the door is opened. Hidden evaporator to guarantee higher storage capacity and less corrosion problems. Built-in refrigeration unit; ventilated operation; Interior LED light. For ambient temperatures up to 43 °C. CFC and HCFC free. R290 highly ecological refrigerant type, cyclopentane gas in foam. Supplied with 5 x 520X442mm Rilsan coated grids and n. 5 sets of 2 stainless steel grid runners. Prearranged to fit RS485 port to facilitate connection to a remote computer and integrated HACCP systems.

### Main Features

- Large digital white-digit display with humidity selection button (3 preset level), cabinet temperature display and setting and turbo frost cycle (to rapidly cool warm loads).
- Fully compliant HACCP digital control: when temperature exceeds critical limits, acoustic and visual alarms are activated. Up to two months of event are kept in memory.
- Large storage area suitable to contain 520x442 mm grids or shelves to improve net capacity.
- Optimized airflow within the chamber guarantees uniformity of temperature on all grids.
- Frost Watch Control: fully automatic defrost starts only when ice is actually building-up in the evaporator and adapt the defrosting duration to guarantee perfect ice removal while optimizing energy efficiency consumption.
- CFC and HCFC free, highly ecological refrigerant type: R290 (ecological gas in foam: cyclopentane). Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3), to reduce green house and ozone depletion effects.
- Hidden evaporator thus guaranteeing higher storage capacity and less corrosion problems.
- Greater storage space: internal structure with numerous charging positions available to host grids, ensuring higher net capacity.
- Adjustable temperature range from 0°C to +10° C.
- Insulation thickness: 65 mm of polyurethane injected with ecological foaming gas cyclopentane to ensure effective insulation with minimum energy consumption (thermal conductivity: 0,020 W/m\*K).
- Removable triple-chamber balloon magnetic gasket to improve insulation and reduce energy consumption and ease of cleaning.
- Cleaning-free condenser: the structure of the wire frame condenser prevents dust and grease accumulation thus avoiding periodical cleaning operations and reducing energy consumption.
- Optical door microswitch to stop the fan once the door is opened, thus minimizing energy waste.
- Model requires only 1 phase 230V/50Hz supply and can be plugged straight into an existing power socket.
- Interior LED light to save energy and for best internal visibility.
- Automatic evaporation of the defrosting water by hot gas on the top for energy saving.
- Prearranged to fit RS485 port to facilitate

APPROVAL: \_\_\_\_\_

connection to a remote computer and integrated HACCP systems.

- Complies with main international certification bodies and is CE marked.
- High resistance foot pedal included.
- Self closing and on site reversible left/right doors.
- Prearranged for remote alarm.
- Low noise level.
- ECA listed.
- IPX5 frontal water protection.
- Tropicalized unit (43°C ambient temperature).
- This appliance is intended for use in ambient temperatures up to 40°C.
- Connectivity ready for real time access to connected appliances from remote and data monitoring (requires optional accessory).

### Construction

- Stainless steel AISI 304 external panels (galvanized external back).
- Inner cell with rounded corners, bottom pressed in only one piece.
- Stainless steel runners and supports easily disassembled.
- Internal components removable without the use of tools to facilitate cleaning operations.
- Pressed stainless steel door handle without joints gathering dust and dirt.
- Easy access to the main components for maintenance.
- Developed and produced in ISO 9001 and ISO 14001 certified factory.


### Included Accessories

- 1 of Pedal opening for cabinets PNC 880324
- 5 of Pair of runners for 470 and 720lt prostore cabinets PNC 880335
- 5 of Rilsan-coated grid 520x442mm for Prostore 470l PNC 880342


### Optional Accessories

- Ethernet connector for IR33 (CAREL) Refrigerated Cabinets and Counters PNC 880252
- Stainless steel grid (520x442) PNC 880321
- Pedal opening for cabinets PNC 880324
- Kit 4 feet, height 200mm PNC 880325
- Kit of 4 feet-h=67 (marine) PNC 880326
- Kit pair of runners (marine) PNC 880327
- Base frame for 1/1 GN rack for 470lt prostore PNC 880328
- Pair of runners for 470 and 720lt prostore cabinets PNC 880335
- Rilsan-coated grid 520x442mm for Prostore PNC 880342  470l

Front




Side



EI = Electrical inlet (power)

Top



### Electric

**Supply voltage:**

691344 (PS04R1FHC) 220-240 V/1 ph/50 Hz

**Electrical power max.:**

0.18 kW

### Key Information:

<b>Gross capacity:</b>	470 lt
<b>Net Volume:</b>	317 lt
<b>Door hinges:</b>	Right Side
<b>External dimensions, Width:</b>	600 mm
<b>External dimensions, Height:</b>	2040 mm
<b>External dimensions, Depth:</b>	700 mm
<b>External dimensions, Depth with Doors Open:</b>	1226 mm
<b>Number and type of doors:</b>	1 Full
<b>Internal Dimensions (depth):</b>	582 mm
<b>Internal Dimensions (height):</b>	1474 mm
<b>Internal Dimensions (width):</b>	472 mm
<b>Noise level:</b>	57.5 dBA
<b>Height adjustment:</b>	15/40 mm
<b>Number and type of grids (included):</b>	5 - 520x442
<b>Type of external material:</b>	304 AISI
<b>Type of internal material:</b>	304 AISI
<b>Number of positions &amp; pitch:</b>	44; 22 mm

### Refrigeration Data


<b>Control type:</b>	Digital
<b>Compressor power:</b>	1/4 hp
<b>Refrigerant type:</b>	R290
<b>Refrigeration power:</b>	406 W
<b>Refrigeration power at evaporation temperature:</b>	-10 °C
<b>Refrigerant weight:</b>	85 g
<b>Operating temperature min.:</b>	0 °C
<b>Operating temperature max.:</b>	10 °C
<b>Operating mode:</b>	Ventilated
<b>Cooling unit:</b>	Built-In
<b>Defrost type:</b>	By Air

### Product Information (EU Regulation 2015/1094)

<b>Energy Class:</b>	C
<b>Yearly and daily energy consumption:</b>	473kWh/year - 1kWh/24h
<b>Climate class:</b>	Heavy Duty (5)
<b>Energy Efficiency Index (EEI):</b>	41.87
<b>Type of model:</b>	vertical chilled

 Prostore 500  
 1 Door Digital Refrigerator, 470lt (0/+10 °C) - R290

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.



### EU energy labelling from 1st July 2016

The European energy labelling scheme for professional refrigerators and freezers is based on requirements setting Minimum Energy Performance standards for commercial refrigeration cabinets sold within the EU. These requirements are designed to drive energy efficiency and environmentally friendly approach for professionals. The European energy labelling scheme will apply to all manufacturers and importers who sell and market products within the EU and it is mandatory across Europe. Important: all products which consume energy above the minimum level will not be able to be sold within the EU from 1 July 2016.

SI 2020 No. 1528.

Important: all products which consume energy above the minimum level will not be able to be sold within the EU from 1 July 2016.

