



SUC-27R
SUC-27F

SUC-48R
SUC-48F

SUC-60R
SUC-60F

SUC-72R

	SUC-27R SUC-27F	SUC-48R SUC-48F	SUC-60R SUC-60F	SUC-72R
Door	1	2	2	3
Shelves	1	2	2	3
Exterior Dimensions (L x D x H)	27 x 29 ½ x 34	47 ¼ x 29 ½ x 34	60 ¼ x 29 ½ x 34	72 x 29 ½ x 34
Capacity cu.ft.	6.3	12	15	15.5
HP	1/4 1/2	1/3 1/2	1/3 1/2	1/2
Voltage	115/60/1	115/60/1	115/60/1	115/60/1
Amps	4.3 6.3	8 7.2	6.9 7.2	9
Nema Config	5-15P	5-15P	5-15P	5-15P
Crated/Uncrated Weight	207/169 lb 216/178 lb	275/238 lb 290/251 lb	323/275 lb 341/290 lb	407/330 lb

- Stainless steel interior and exterior with aluminum finished back
- Rounded corner design for easy cleaning of inside storage
- Positive seal self-closing door(s) with 90 degrees stay open feature
- Magnetic door gasket(s) with no tools removal for easy cleaning
- Refrigeration system holds 33°F to 41°F (0.5°C to 5°C) or -8°F to 0°F (-22°C to -18°C) for optimum food preservation
- Electronic control system: Adjustable temperature set point and defrost frequency as well as error codes to diagnose service issues
- Adjustable, heavy duty PVC coated shelves
- Standard heavy duty casters make it easy to move and clean underneath
- Condensing unit access in back of cabinet, slides out for easy maintenance

* Specifications subject to change without notice.

