



Did You Know?

According to the EPA, 31% of water used by restaurant or food service establishments takes place in restrooms. For more info, go to www.epa.gov/watersense.



CALIFORNIA
Energy Commission - (CEC)
Compliant Models Available
Call for more Info.

- Water & Energy Conservation (0.5 gpm flow rate)
- Minimum Sensor Range: 3 5/32"
- Maximum Sensor Range: 11 13/16"
- 2 Year Warranty
- Lead Free Product
- Maximum Operating Temperature 40-158°F
- Operating Pressure: 7-100 PSI
- Security Time: The faucet will shut down automatically after 90 sec.
- Single Hole Chrome Plated Touch Free Faucet for Cold or Premixed Water



BKF-JET-G



See Page 8 for details.

BKF-JET-G - Jet Faucet

- Available with a 9V Battery or a 9V Transformer
- Adjustable Sensor Settings by Remote Control (Sold Separately)



Part Number Power Supply

BKF-JET-9B-G	Battery
BKF-JET-9T-G	Transformer
BKF-JET-9H-G	Hardwire



BKF-KAI-G



See Page 8 for details.

BKF-KAI-G - Kai Faucet

- Available with a 9V Battery or a 9V Transformer
- Adjustable Sensor Settings by Remote Control (Sold Separately)



Part Number Power Supply

BKF-KAI-9B-G	Battery
BKF-KAI-9T-G	Transformer
BKF-KAI-9H-G	Hardwire



BKF-CAS-G

BKF-CAS-G - Cascade Faucet

- Integrated Plate to Cover Existing Holes
- Dual Power Input Box Unit that Allows Operating the Integrated Battery Backup, for Normal Use During Power Supply Failures, when a 9V Battery is Added (Lithium Battery Recommended)



Part Number Power Supply

BKF-CAS-9B-G	Battery
BKF-CAS-9T-G	Transformer
BKF-CAS-9H-G	Hardwire

Splash/Deck Mount Electronic Faucet



SHOWN AS:
BKF-SEF-3G

- 3 1/2" Gooseneck Spout
- Adjustable Temp. Setting
- Optional Low-Flow Aerator

- Battery or Plug-In Power Supply Options

Part Number	Spout Mounting
BKF-SEF-3G	Splash
BKF-DEF-3G	Deck



SHOWN AS:
BKF-DEF-3G