

Project

Quantity

Item #

Model Specified:

CSI Section 11400

"Extra-Wide" One Reach-In Refrigerator Models/Self-Contained



Model Shown One Section

One Section Models, 32" Deep

Stainless Exterior
& Interior

1-Section Full Length Door Model

RHT132EUT-FHS

1-Section Half Length Door Model

RHT132EUT-HHS

Stainless Exterior,
Anodized Alumi-
num Interior

1-Section Full Length Door Model

AHT132EUT-FHS

1-Section Half Length Door Model

AHT132EUT-HHS

These "Extra-Wide" reach-in refrigerator models are specially designed to accommodate the use of standard 26" wide x 18" deep meat lugs. Each is supplied standard with such high quality features as balanced refrigeration systems, microprocessor controls, and stainless steel exteriors. Additionally, they offer the widest range of optional accessories to choose from, and can be specified for use with many different applications, including: Foodservice, Correctional, Institutional, Export, etc.

Standard Product Features

- Traulsen's Smart Control With LED Display
- StayClear™ Condenser
- R-Series: Stainless Steel Exterior & Interior
- A-Series: Stainless Steel Exterior/Anodized Aluminum Interior
- Self-Contained Refrigeration System Using R-450A
- Half Length Stainless Steel Doors With Locks & LED Lights
- Self-Closing Doors With Stay Open Feature At 120°
- Guaranteed For Life Cam-Lift Hinges
- Standard Door Hinging: Right (other hings available)
- Automatically Activated Lights, Doors with embedded LED lights when door is open
- Stainless Steel Breaker Caps
- Three Adjustable Plated Shelves Per Section, Supported On Shelf Pins (installed at the factory)
- Requires Floor Drain
- Magnetic Snap-In EZ-Clean Door Gasket(s)
- Gasket-Protecting Metal Door Liner
- Thermostatic Expansion Valve Metering Device
- Stainless Steel One-Piece Louver Assembly
- 9' Cord & Plug Attached
- Set of Four (4) 6" High Adjustable Stainless Steel Legs
- Three Year Parts And Labor Warranty
- Five Year Compressor Warranty

Standard Product Features

- Optional Voltage: 220/50/1 or 208/115/1
- Remote For Use With 20°F Glycol System
- Remote Applications
- Re-Hinging Feature For Door(s)
- Universal Type Tray Slides To Accommodate Either (1) 26" x 18" Meat Lug or (1) 18" x 26" Sheet Pan (lengthwise)
- Additional Plated Shelves
- Stainless Steel Shelves
- Locking Hasps (padlocks supplied by others)
- Marine Positive Latch
- EZ-Open Foot Pedal (full height doors only)
- Recessed or Relocate Electrical Outlet Box Options
- Kool Klad Exterior Laminate Decor
- 4-1/2" High Stainless Steel Base In Lieu of Legs
- Stainless Steel Finished Back With Rear Louver
- Clear Glass Door(s) In Place Of One Or More Solid Door(s)
- Set of Four (4) 6" High Casters
- Set of Four (4) 4-5/8" High Casters
- 6" High Stainless Steel Kick Plate (for use with standard legs)
- Set of Four (4) 6" Stainless Steel Flanged Legs
- Prison/Correctional Facilities Options



Listed by Underwriters Laboratories Inc.,
to U.S. and Canadian safety standards and
Listed by NSF International.

3-YEAR
PARTS & LABOR WARRANTY

Approval: _____

TRAULSEN
4401 BLUE MOUND RD.
PHONE 1 (800) 825-8220
Website: www.traulsen.com

FT. WORTH, TX 76106
FAX-MKTG. 1 (817) 624-4302

Traulsen

Project

Quantity

Item #

Model Specified:

CSI Section 11400

Specifications

Construction, Hardware and Insulation

Cabinet exterior front, one piece sides, louver assembly and doors are constructed of heavy gauge stainless steel. Cabinet interior and door liners are also constructed of heavy gauge stainless steel (anodized aluminum in the A-Series). The exterior cabinet top, back and bottom are constructed of heavy gauge galvanized steel. A set of four (4) adjustable 6" high stainless steel legs are included.

Removeable plug cylinder locks and guaranteed for life cam-lift, gravity action, self-closing metal, glide hinges with stay open feature at 120°. Hinges include a concealed switch to automatically activate the interior lighting. Guaranteed for life. Doors have seamless, polished metal corners.

Gasket profile and material simplify cleaning and increase overall gasket life. Anti-condensate heaters are located behind each door opening.

Both the cabinet and door(s) are insulated with an average of 2" thick high density, non-CFC, foamed in place polyurethane.

DIMENSIONAL DATA	R/AHT132EUT
Net capacity cu. ft.	26.0 (737 cu l)
Length - overall in.	32 (81.3 cm)
Depth - overall in.	35 (88.8 cm)
Depth - less handle in.	33¾ (84.4 cm)
Depth - over body in.	32 (81.3 cm)
Clear door width in.	26½ (53.6 cm)
Clear half-door height in.	27⅓/₁₆ (69.5 cm)
Clear full-door height in.	58⅝ (146.5 cm)
Height - overall on 6" legs	83¼ (211.5 cm)
RHT Net Wt. lbs.	400 (180 kg)
No. Standard Shelves	3
Shelf area sq. ft. ¹	18.8 (1.75 sq m)
ELECTRICAL DATA	
Voltage	115/60/1
Feed wires with Ground	3
Full load amperes	16
REFRIGERATION DATA	
Refrigerant	R-450A
Refrigerant Charge Amount	16 oz
BTU/HR H.P. ²	4200 (½HP)

NOTES

NOTE: Figures in parentheses reflect metric equivalents.

1= Area of standard shelf complement only, does not include storage area of additional shelves or available on cabinet bottom.

2= Based on a 90°F ambient and 20°F evaporator.

4= 12" Top clearance required for optimum performance and service access.



Equipped With One NEMA 5-20 P Plug

NOTE: Full load amps and plug style may vary depending on electrical options chosen and condensing unit employed.

Refrigeration System

A top mounted, self-contained, high capacity refrigeration system using environmentally friendly, non-flammable R-450A refrigerant is conveniently located behind the one piece louver assembly. It features a finless StayClear™ condenser, thermostatic expansion valve, air-cooled hermetic compressor. A 9' cord and plug is provided. Standard operating temperature is 34 to 38°F.

Controller



Traulsen's Smart Control features advanced control algorithms and sophisticated diagnostic capabilities. Smart sensors will adapt the operation of the refrigeration system to a variety of environments and usage patterns. The Smart Control offers a complete set of visual alarms designed to alert the user to critical events. In the event of an alarm, a dedicated Alarm LED will illuminate, informing the user of the critical event and describing the event in the large, easy to read full text display.

Interior

Standard interior arrangements include three (3) plated shelves per section, mounted on shelf pins. Shelves are full-width, and do not have any large gaps between them requiring the use of "bridge" or "junior shelves". Recommended load limit per shelf should not exceed 225 lbs. Optional tray slides may be purchased in combination with, or in lieu of these. Interior arrangements are installed at the factory.

Warranties

Both a three year parts and labor warranty and a five year compressor warranty (self-contained models only) are provided standard.



Note: Product drawings shown with optional 6" high casters.

NOTE: When ordering please specify: Voltage, Hinging, Door Size, Options and any additional warranties.

Continued product development may necessitate specification changes without notice.

Part No. TR35847 (REV. 09-22-21)

TRAULSEN
4401 BLUE MOUND RD.
PHONE 1 (800) 825-8220
Website: www.traulsen.com

FT. WORTH, TX 76106
FAX-MKTG. 1 (817) 624-4302

Traulsen