

24" Depth Direct Draw Beer Dispenser



SDD-24-48

SDD-24-60

SDD-24-72

	SDD-24-48	SDD-24-60	SDD-24-72
Doors	2	2	3
Exterior Dimensions (L x D x H)	48 7/8 x 24 3/8 x 35 5/8	60 3/4 x 24 3/8 x 35 5/8	72 3/4 x 24 3/8 x 35 5/8
Capacity 1/2 Barrels	2	2	3
HP	1/3+	1/3+	1/3+
Voltage	115/60/1	115/60/1	115/60/1
Amps	6.4	6.4	7.4
Nema Config	5-15P	5-15P	5-15P
Crated/Uncrated Weight	231/216 lb	290/255lb	352/310 lb

- Standard cabinet exterior construction includes attractive, wear resistant vinyl on steel in black finish
- Standard interior construction utilizes stainless steel walls, floor and ceiling
- Refrigeration system uses R134a Refrigerant which is CFC and HCFC-free for compliance with environmental safety concerns
- Oversized, factory balanced, refrigeration system holds 33°F to 38°F (0.5°C to 3.3°C)
- NSF-7 approved for packaged and bottled product
- LED lighting: Visibility of products, last longer and consume low energy
- Digital temperature control: Adjustable temperature set point and defrost frequency as well as error codes to diagnose service issues
- Easily accessible condenser coil for cleaning and easy service access
- Designed to accommodate a variety of beer kegs
- Self –Closing/Lockable doors: Positive seal, self-closing door(s) to help conserve energy and security

* Specifications subject to change without notice

