Model:

Underbar Refrigeration:

STDD-30-23

Mobility Direct Draw Beer Dispenser





STDD-30-23

- CABINET CONSTRUCTION
 Standard, cabinet exterior
 construction includes attractive, wear
 resistant vinyl on steel in black finish.
 Stainless exterior options available.
 Standard interior construction utilizes
 stainless steel walls, floor and ceiling.
- REFRIGERATION
 Refrigeration system uses R134a
 refrigerant, which is CFC and
 HCFC-free for compliance with environmental safety concerns.
- ELECTRICAL
 Units wired at factory and ready for connection to a 115/60/1 phase,
 15 amp dedicated outlet.
- TEMPERATURE
 Oversized, factory balanced,
 refrigeration system holds 33°F to
 38°F (0.5°C to 3.3°C)
- SANITATION
 NSF-7 approved for packaged and bottled product.

MODEL FEATURES:

- Standard casters for mobility
- Self-closing doors with key lock
- Reinforced stainless steel interior floor
- Side knock out plugs for gas lines
- Designed to accommodate a variety of beer kegs

General Specification

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

		Cabinet Dimensions (inches / mm)							
Model	Doors	L	D	Н	Capacity 1/2 Barrels	HP	Voltage	Amps	NEMA Config.
STDD-30-23	1	23 1/2 596	30 3/4" 782	38 3/4 984	1	1/6+	115/60/1	1.7	5-15P (i)

Height does not include 15 1/4" (388mm) for draft arm.





Plug type varies by country.

Two-faucets column is option

SABA

Add: 3390 Enterprise Avenue, Hayward, CA 94545

Tel: (510) 293-0189 Fax: (510) 293-0199 E-mail: info@sabacorpusa.com Website: www.sabacorpusa.com



