



HOSHIZAKI

ACF-180DG-LRR-RRS-C1 U

3-Section Freezer Counter with 100mm splashback



PRODUCT SERIES: ADVANCE
ITEM NUMBER: 899020865
COUNTRY OF ORIGIN: TURKEY

Hoshizaki Advance ACF-180DG-LRR-RRS-C1 U is a 3-section 1/1 GN freezer counter with three doors and a flat worktop with 100mm splashback. It has a net usable volume of 257 ltr. The height excluding castors is 800mm. The total height including castors and 100mm splashback is 950mm. Castors = H 150mm (C1). Shelf width is 325mm.

- Fan assisted cooling
- Automatic defrost with re-evaporation of defrost water
- Heavy duty cabinet and compressor compartment construction
- Climate class 5 cooling system enduring up to +40°C ambient temperature
- Exterior and interior of stainless steel
- Compartmentalized cooling unit that is available as one unit
- A compact slide out refrigeration unit for maintenance and service
- Removable condenser filter for cleaning or replacement
- Reversible doors
- Anti-tilt shelves
- Removable magnetic door gaskets with triple insulation area
- Pan-shaped inside base with rounded corners to catch fluids
- IP 21 water protection
- Matching design identity as the Advance cabinets



1 / 1 GN

ACCESSORIES INCLUDED

2 grey shelves per door section

OPTIONAL EXTRAS

Set of legs 130-180mm (L1)
Set of legs 135-200mm (L2)
Set of 4 Castors for 900mm Counter-top (C2)
Castor Extension Kit (extends height of castors by 50mm)
Flat worktop
Shelf support - Left
Shelf support - Right
Stainless shelf
Grey shelf

WARRANTY PERIOD

5 Years on Parts & Labour

EXTERIOR

Stainless Steel

INTERIOR

Stainless steel

Refrigerant type: R290 / Refrigerant: 0.06 kg / CO2 equivalent: 0.18 kg

CERTIFICATIONS



Energy consumption	Energy efficiency class	Energy efficiency class standard	Energy Efficiency Index (EEI)
2,892 kWh/year	D	ISO 22041-2019	74.53 EEI

ACF-180DG-LRR-RRS-C1 U



TECHNICAL SPECIFICATIONS

Temperature range	Shelf size	Volume, gross	Net usable volume	Power supply	Connection load	Climate class	Ref. capacity - at -30°C
-22/-5°C	1/1 GN	457 l	257 l	230V, 50Hz	639 W	5 (max. ambient 40°C w/ 40% RH)	506 W

SHIPPING SPECIFICATIONS

Width (packed)	Depth (packed)	Height (packed)	Volume (packed)	Gross weight	Width	Depth	Height	Net weight
1,870 mm	820 mm	1,050 mm	1.61 m3	142 kg	1,780 mm	700 mm	950 mm	130 kg

Disclaimer: Every effort has been made to ensure that the information contained in this spec sheet is accurate at the time of publishing. Hoshizaki Europe BV assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.



SECTION B-B

