

# BANQUETING TECHNICAL DATASHEET

## MHC10 HEATED CABINET



## MHC16 HEATED CABINET



## MRC16 CHILLED CABINET



### MHC10

Dimensions (mm)	External	Internal
Width	807	587
Depth	885	653
Height	1372	925
Door Opening		-
<b>Capacity</b>		
Capacity cu.ft/ltrs	13.77/390	

### MHC16

Dimensions (mm)	External	Internal
Width	807	587
Depth	885	653
Height	1770	1322
Door Opening		-
<b>Capacity</b>		
Capacity cu.ft/ltrs	19.4/549	

### MRC16

Dimensions (mm)	External	Internal
Width	803	567
Depth	900	660
Height	2013	1332
Door Opening		567
<b>Capacity</b>		
Capacity cu.ft/ltrs	18.5/523	

## KEY FEATURES

- Foodsafe stainless steel exterior and interior
- Easy to clean dished base with radiused corners (MRC16 only)
- Self closing doors
- Barrel locked doors
- Removable racking system
- Precision injected, high density polyurethane insulation with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential).
- Heavy duty, non-marking swivel castors with brakes
- Built in handles at side for easy mobility
- All round bumper for added protection during transfer of cabinet
- Transports quantities of food from kitchen to servery/banqueting area
- **MHC:** Hot food remains in first class condition with minimal dehydration
- **MHC:** Designed to keep food hot above 70°C for up to 1 hour after switching off



# BANQUETING TECHNICAL DATA

	MHC10	MHC16	MRC16
Temperature (°C)	+78/+83°C	+78/+83°C	+1/+4°C
Climate Class	-	-	Class 4 (30°C)
Power Supply	240V/50Hz/1Ph	240V/50Hz/1Ph	230V/50Hz/1Ph
Fuse (Amps)	-	-	13
Defrost	-	-	Automatic Off Cycle
Noise level (dBA)	-	-	59
<b>Fittings</b>			
Shelves	10	16	16
Trayslides per section	20	32	32
<b>Electrical / Energy Data - Hydrocarbon Refrigerant</b>			
Refrigerant	-	-	R290
Energy Efficiency Class	-	-	D
Energy Consumption (kW / 24hrs)	-	-	1.91
Start Up (Amps)	-	-	9.5
Running (Amps)	-	-	1.67
Heat Rejection	-	-	484 W

## IMPORTANT NOTES:

\*Energy consumption is tested to EN16825 in 24hrs (MRC16 only)

\*\*\*Heat rejection is evaporating at -10°C in 32°C Ambient

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration  
Bryggen Road,  
North Lynn Industrial Estate  
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000  
Spares: +44(0) 1553 817 017  
E info@williams-refrigeration.co.uk  
W www.williams-refrigeration.co.uk

