



# Induced Energy

## CS3000DF-P Induction Cooking Unit

Suitable for drop-in through lava stone invisible unit



### Product Specifications

<b>Maximum Power</b>	3.0kW
<b>Electrical Supply</b>	230V AC 50Hz (50 - 60Hz also available). 13 amp single phase supply
<b>Cord &amp; Plug</b>	Cord length 1.8m Moulded 13-amp plug fitted (UK) Appropriate plug for each export market
<b>Weight</b>	9.5kg
<b>Dimensions (mm)</b>	Drop-in case: 395 x 395 x 170mm Front control panel: 350 x 90mm (Alt Vent system available)
<b>Depth of Field</b>	Up to 30mm
<b>Safety Features</b>	Pan detection; boil-dry protection; overheat prevention; clean filter warning
<b>User Interface</b>	Display panel: Clean filter warning; No Pan Present warning; Glass/Lava hot warning; Shutdown
<b>Controls</b>	Ergonomically designed knob with precise settings of 1 to 25
<b>Bespoke Options</b>	Overall design/size, Lava options, natural or coloured glazed
<b>Warranty</b>	2 years parts and labour, excluding lava stone top
<b>CE</b>	Approved
<b>Stone</b>	Maximum thickness of stone is 15mm. Lava stone is recommended

*Induced Energy Ltd. Operate a continuous programme of product development and improvement. Product specifications may therefore be subject to change.*

Induced Energy Ltd, Westminster Road, Brackley, Northants NN13 7EB  
Tel: 01280 875400 Email: sales@inducedenergy.com