



UTENSIL WASHER UX-750BCV 230-400/50/3N DD

Rack size 780 mm x 700 mm and door clearance 820 mm. Constant temperature rinsing system. HRS system.

1303533



WARE WASHING
POT WASHERS

SALES DESCRIPTION

Door clearance 820 mm.
Equipped with a steam condenser.

Ideal to wash big sized pots and wares.

- ✓ Powerful and high pressure: specially indicated for restaurants, ice-cream shops, pastries and butcheries.
- ✓ Constructed from stainless steel.
- ✓ Door divided in two parts, perfectly counterbalanced, easy to handle.
- ✓ Double skinned machines: silent working and reduced thermal dispersions.
- ✓ Wash tank without corners to avoid dirt accumulation in angles.
- ✓ Stamped wash dispersers in stainless steel tubes.
- ✓ Easy to remove wash- and rinse dispersers.
- ✓ Safety micro switch at the door and electronic safety device to guarantee washing temperature and time.
- ✓ Advanced LCD control panel with humidity protection. Display of wash and rinse temperatures.
- ✓ Reduced water consumption.

INCLUDES

- ✓ 1 stainless steel basket and insert for 4 trays.
- ✓ Adjustable detergent and rinse aid dosing equipment.
- ✓ HRS system: steam condenser.

OPTIONAL

- Stainless basket.
- Drainage pump with level sensor. Proactive tank water renewal.
- Stainless carrier for trays.

ACCESSORIES

- Stainless steel baskets
- Dosing equipments
- Manual water softeners
- Carrier for trays
- Automatic water softeners

SPECIFICATIONS

Basket dimensions: 780 mm x 700 mm
 Stainless steel basket: 1
 Equipment: supplementary trays: 1
 Useful height: 820 mm
 Cycles: 5
 Cycle duration: 120/180/240/360/480"
 Production baskets / hour: 30/20/15/10/7
 Electrical supply: 3N V / 50 Hz /
 Electrical connection: .

Loading

- ✓ Pump: 3.2 Hp / 2400 W
- ✓ Tank: 6000 W
- ✓ Boiler: 9000 W
- ✓ Total loading: 11400 W
- Feed water temperature: 10°C - 60°C
- Wash temperature: 40°C - 70°C
- Rinse temperature: 70°C - 87°C
- Wash tank capacity: 75 l
- Boiler capacity: 12 l
- Water consumption/cycle: 4 l
- Drainage base maximum height: 185 mm
- Drain diameter: 30 mm

External dimensions (W x D x H)

- ✓ Width: 922 mm
- ✓ Depth (closed): 932 mm
- ✓ Depth (open): 1400 mm
- ✓ Height (closed): 2165 mm
- ✓ Height (open): 2300 mm
- Net weight: 252 kg
- Noise level (1m.): 76 dB(A)
- Crated dimensions
960 x 1062 x 2190 mm
- Gross weight: 264.5 kg






UTENSIL WASHER UX-750BCV 230-400/50/3N DD

Rack size 780 mm x 700 mm and door clearance 820 mm. Constant temperature rinsing system. HRS system.



1303533

WARE WASHING
POT WASHERS



- A - Water inlet 3/4" GAS
- B - Drain tube ø30 mm
- C - Connection cable



sammic.co.uk

Food Service Equipment Manufacturer

Unit 2, Trevanth Road

Troon Industrial Park

LE4 9LS - Leicester

uksales@sammic.com

Tel.: +44 0116 246 1900



Project

Date

Item

Qty

Approved

product sheet
updated 03/12/2025