

REFRIGERATOR MANUFACTURER
Turbo air
 more durable, efficient, beautiful

4184 E. Conant St.
 Long Beach, CA 90808
 Tel. 310-900-1000
 Fax. 310-900-1077
www.turboairinc.com

Project:	
Model #:	
Item #:	
Available W/H:	Qty:
Approval:	
ALA #:	SIS #:
CSI Section 11400	

Vertical Open Display Cases

Extra Deep
 Glass or Solid Side Panel

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.

Model : TOM-36DXB-N
TOM-36DXB-SP(-A)-N



W/ Security cover (optional)



TOM-36DXB-N



TOM-36DXB-SP-N



TOM-36DXB-SP-A-N

FEATURES & BENEFITS

■ Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

■ Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

■ Modern design

By integrating great contours with durable structures, our modern style product designs are user-friendly while maintaining the highest product visibility and aesthetics. Safety reinforced tempered glass front shield and side walls optimize the merchandiser's display effects of fresh salads, sandwiches, desserts and beverages. Its elegant contemporary euro design will enhance any store application.

■ LED interior lighting under each shelf

■ Designed to enhance impulsive sales

Ideal for eye-catching displays and convenient access with fast service in high traffic area.

■ Standard back-guard improves airflow

■ Energy saving night curtain standard

■ Optional security cover available

■ Foamed with polyurethane, high-density cell insulation (CFC free)

■ Perforated interior back wall and top for improved airflow

■ Front air intake and rear air discharge

■ Solid side panel with stainless steel interior (SP-N) or black coated interior (SP-A-N) option (lead time applies)

NATURAL
 Refrigerant

ETL
 Intertek

ETL
 Intertek

2 YEAR
 WARRANTY

Compressor
 5 YEAR
 WARRANTY

Model	CU./FT.	# of Shelves	HP	AMPS	Crated Weight (lbs.)	L x D x H [†] (inches)
TOM-36DXB-N TOM-36DXB-SP(-A)-N	17.1	4	3/4 x 2	15.5	631	355/8 x 33 1/4 x 78 3/8

*Extra Deep
Glass or Solid Side Panel*

Model : TOM-36DXB-N
TOM-36DXB-SP(-A)-N

ELECTRICAL DATA	
Voltage	115/60/1
Plug Type	 NEMA 5-20P
Full Load Amperes	15.5
Compressor HP	3/4 x 2
Cord Length (ft.)	97/8
Refrigerant	R-290
DIMENSIONAL DATA	
Net Capacity (cu. ft.)	17.1
Ext. Dimension (L x D x H†) (in.)	355/8 x 331¼ x 783/8
Int. Dimension (L x D x H) (in.)	331¼ x 211¼ x 483/4
# of Shelves	4
Shelf Size (L x D) (in.)	331/8 x 16
Net Weight (lbs.)	488
Gross Weight (lbs.)	631

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

* Depth does not include 1-5/8" for safety bar and 1-1/8" for rear spacers.

† Height does not include 5/8" for bolt height.

■ **WARRANTY :** 2 Year Parts and Labor Warranty
Additional 3 Year Warranty on Compressor

■ STANDARD FEATURES

- ***Simple plug-in installation***
- ***Patented self-contained system, no plumbing required***
- ***Solar powered digital thermometer***
- ***Digital electronic thermostat with defrost control***
- ***Bolt height adjustable up to 2¾"***
- ***Standard color comes in black only***

** Lead time applies. Please contact your sales representative for more details to order.

■ **Recommended operating conditions**

TOM models are designed to operate in an environment where temperature & humidity do not exceed 80°F and 55% respectively.

Units should not be installed near HVAC vents, fans or doorways that will disrupt the air curtain and compromise the function of the cabinet.

Air curtain models will run most efficiently when completely loaded with product. When used as a built-in, required clearance for the rear is 4" and the top is 5".


■ OPTIONAL ACCESSORIES

- 1.6" caster: CAS16WBT00 (non-brake)
- 4" caster, ½" diameter & 13 TPI: 30265L0400 (non-brake), 30265L0300 (w/ brake)
- 6" leveling seismic leg (½", 13 TPI): 30221M0700
- Security cover: SC-36-DXB, SCM-36-DXB, SCS-36-DX
- Price tag channel: P36DX000ZK (33"L)


Ver.20260909

PLAN VIEW


(unit : inch)



TOP VIEW



FRONT VIEW



SIDE VIEW



■ **Turbo Air:** 800-627-0032 ■ **Bake Tech Innovation:** 800-500-3519
■ **Warranty:** 800-381-7770 ■ **AC:** 888-900-1002

TURBO REFRIGERATOR MANUFACTURER
Turbo air



Turbo air REFRIGERATION SYSTEM **Texaking**

Continued product development may necessitate specification changes without notice.