

Product data sheet – Gas griddle plate 1 smooth

MKN-No.:
1261101

Cooking appliance according to DIN 18852 for application in the commercial preparation of food in the general catering industry, front cooking, free flow systems and snack bars. For cooking with contact heat, for frying of quick-fried pieces, starch side dishes, egg dishes, desserts such as pancakes and for grilling.



Technical highlights

Material:

Casing and cover are made completely of CNS (material No. 1.4301) / AISI 304.
Visible surfaces with polished and satin finish, 320 grit.

Bendings:

Cover bent downwards 30 mm at the front and bent upwards 20 mm at the rear. Designed as a drip edge at the front. 50 mm cover projection closed to the appliance body.

Body:

Buckling resistant, self-supporting, closed construction with side walls, rear wall and bottom.

Control panel:

Operation panel desk-shaped for highest ergonomic requirements and very easy cleaning. Removable from the front for easy and cost efficient service access.
Ergonomiacally shaped knobs for a easy identification of the position.

Effective area:

Griddle plate with large radii which are easy to clean, seamless and greaseproof, recessed and welded into the cover plate. One adjustable heating zone. Closable fat drain outlet at the front with a removable fat collecting container beneath it.

Installation:

Equipped for installation of a 580 mm high Counter SL lower section with removable appliance feet (150 mm high) which are adjustable in height.

Type of energy:

Appliance is completely tubed internally in accordance with gas requirements. Gas connection by means of a gas appliance tube attached to a gas socket (DN 15) with shut-off valve.

Special feature:

Heating:

Heating by atmospheric linear burners, thermoelectrically protected. Piezo ignition for the ignition burners to start up the main burner.

Product data sheet – Gas griddle plate 1 smooth

MKN-No.:
1261101

Cooking appliance for frying of quick-fried pieces, starch side dishes, egg dishes, desserts such as pancakes and for grilling.

Current drawings you will find here:
www.mkn.com
 ▶ Partner Login
 ▶ spare parts database & download

Further features

- connection, sealing by means of patented connecting method – clamp bar is rounded (R 20) at the back for easier cleaning
- griddle plate, finely ground, of high temperature resistant steel (1.5415) – 14 mm thick
- thermostatic temperature control with electronic flame monitoring – gas shut off valve installed in appliance for maintenance purposes

Technical data

Dimensions (LxWxH*) (mm):	500 x 700 x 270
Effective area:	1
Dim.: effect. area (LxWxH) (mm):	420 x 545 x
Diameter (mm):	
Nominal capacity (L):	
Nominal fill quantity (L):	
Connected load (electrical) (kW):	
Voltage ¹ (V):	
Recommended fuses (A):	
Frequency range (Hz):	50/60
Rated heat load (kW):	7,0
Standard gas pressure – natural gas ² (mbar):	20; 25
Standard gas pressure – liquid gas ² (mbar):	30; 37; 50
Gas connection:	DN 15 (1/2")
Heat-up time (Min.):	
Vapour pressure (bar):	
Refrigeration capacity (kW):	
Net weight (kg):	50
Gross weight ³ (kg):	58
Heat emission latent (W):	2800
Heat emission sensitive (W):	2450
Type of protection:	

* Carcass height plus optional appliance feet with a height of 150 mm or 200 mm

Product safety

- CE mark

Installation requirements

- gas connection provided by customer

Option / accessories

MKN-No.:	Description:
10018076	griddle plate scraper for smooth and ribbed frying surfaces
10017094	splash guard
201568	all-gas socket, 1/2", with gas tube, 1/2" x 800 mm

¹ special voltages on request

² further types of gas on request

³ seaworthy packing on request