

Caribbean Refrigerated Multi-tier units



Picture shows 1906mm long rear door version.

Product Specification

Dimensions

Model - - - - - Dimensions - - - - - loading

Wall solid back units

CARIB72.719 W - - - 1906 x 850 x 1430mm high - - - 3.4kW

Refrigerant

R404a CFC free refrigerant

Operating conditions

Meets EN ISO 23953 standard, providing M1 cabinet class conditions and exceeding climate class 3 environment of 25°C at RH 60%

Electrical Connection

220V/240V, 1 phase, 50Hz,

Cable: 2 metres with 13 amp plug fitted 1906mm models fitted with cable and 16 amp commando plug

Construction

Top: Stainless Steel, Exterior: Colour plastic coated steel or Stainless steel. Interior: Stainless Steel.

Well Dimensions

1906 model - 1625 x 480 x 170mm

Product Features

- Open fronted display cabinets, achieves a balanced air temperature throughout the cabinet of between 2°C & 5°C in ambient temperatures up to 27°C at a relative humidity of 50%.
- Microprocessor based temperature control with automatic defrost and condensate handling system.
- Three height adjustable and removable shelves for flexibility of display.
- Illuminated display via integral fluorescent lighting.
- Supplied on castors with height adjustable levelling feet for stability.
- Double glazed rear hinged doors or solid back.
- 304 grade stainless steel top and well.
- Ambient under 1600mm & 1900mm rear hinged door models.