Model:

Underbar Refrigeration:

SBB-27-23B

Solid Mobility Swing Door Back Bar Cooler





SBB-27-23B

- CABINET CONSTRUCTION
 Standard, cabinet exterior
 construction includes attractive, wear
 resistant vinyl on steel in black finish.
 Stainless exterior options available.
- Standard interior stainless steel walls, floor and ceiling.
- REFRIGERATION
 Refrigeration system uses R134a
 refrigerant, which is CFC and
 HCFC-free for compliance with environmental safety concerns.
- ELECTRICAL
 Units wired at factory and ready for connection to a 115/60/1 phase,
 15 amp dedicated outlet.
- TEMPERATURE
 Oversized, factory balanced,
 refrigeration system holds 33°F to
 38°F (0.5°C to 3.3°C)
- SANITATION
 NSF-7 approved for packaged and bottled product.

MODEL FEATURES:

- Standard casters for mobility
- Self-closing doors with key lock
- Magnetic door gasket of one piece construction, removable without tools for ease of cleaning.
- Side knock out plugs for gas lines
- Designed to accommodate a variety of beer kegs

General Specification

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

			Cabinet Dimensions					,		·	,
			(inches / mm)			Capacity					
						12 oz.	1/2				
Model	Doors	Shelves	L	D	Н	Cans	Barrels	HP	Voltage	Amps	NEMA Config.
SBB-27-23B	1	2	23 1/2 596	30 3/4 782	38 3/4 984	30 6-pks	1	1/6+	115/60/1	1.7	5-15P (i)





Plug type varies by country.



