



ELECTRIC RETHERMALIZER



IRT-14-E

Shown with optional
casters

IRT-14-E
IRT-18-E



Special stainless steel alloy vessel
withstands strong salt
concentrations.



Stainless steel cooking rack
included

FEATURES

- Water replacement can be adjusted from 1 GAL (3.8 L) per hour to 3 GAL (11 L) per minute depending on specific needs.
- Available with a manual timer or computer controls with multiple time feature for different product drop times.
- Water level sensor.
- Water pressure regulator.

ELECTRIC ELEMENTS

- Firewire heating element is located inside the stainless steel vessel
- Element output is 8.8 KW.

STAINLESS STEEL VESSEL

- Large 18" x 14" (457 x 356 mm) cooking area.
- Vessel sides are robotically welded stainless steel to virtually eliminate leaks.
- 1 1/4" (32 mm) full port drain valve empties frypot quickly and safely.
- Stainless steel cooking rack to hold a variety of bag sizes.
- Vessel is 16 gauge 317 alloy stainless steel.

EXTERIOR FEATURES

- Stainless steel front, door, sides, back and vessel.
- Welded and polished stainless steel seams.
- Full bottom chassis provides structural support.
- Plate mounted 6" (152 mm) heavy duty stainless steel legs or optional casters assure secure support.
- One year parts and labor warranty. Limited warranty on frypot, stainless steel frypot is five years prorated.
- Vessel is 16 gauge 317 alloy stainless steel.




1128 Sherborn Street | Corona, CA 92879 | 800.343.7790 | imperialrange.com | imperialsales@imperialrange.com

© 2026 Imperial Commercial Cooking Equipment Imperial reserves the right to change specifications at any time without prior notice and without any obligation for past or future equipment purchases. Visit www.imperialrange.com for specification updates



ELECTRIC RETHEMALIZER



MODEL	WATER CAPACITY	OVERALL DIMENSIONS			ELECTRICAL OUTPUT	SHIP WEIGHT (KG) LBS
		WIDTH	DEPTH	HEIGHT		
IRT-14-E	12 GAL (45 L)	16" (406)	35" (899)	32" (813)	8.8 KW	(89) 195
IRT-18-E	16 GAL (61 L)	19.5" (495)	35" (899)	32" (813)	8.8 KW	(103) 227

Notes: Measurements in () are metric equivalents.

ELECTRICAL AMPERAGE REQUIREMENTS

MODEL	TOTAL KW	VOLTS	PHASE	AMPS
IRT-14-E / IRT 18-E	8.8	208	3	25
	8.8	240	3	22
	8.8	480*	3	11

*Additional charge

CLEARANCE REQUIREMENTS

For use only on non-combustible floors. Legs or casters are required for non-combustible floors; or 2" (51 mm) overhang is required when curb mounted. Provide 0" clearance from non-combustible surfaces and 6" (152 mm) from combustible surfaces.



MADE IN USA



#40247 Rack Basket



#40248 Suitcase/Envelope



#39387 Basket



#10-39948 Casters
(Set of 4, 2 with brakes)



1128 Sherborn Street | Corona, CA 92879 | 800.343.7790 | imperialrange.com | imperialsales@imperialrange.com

© 2024 Imperial Commercial Cooking Equipment Imperial reserves the right to change specifications at any time without prior notice and without any obligation for past or future equipment purchases. Visit www.imperialrange.com for specification updates