

## HEATED DISPLAY MERCHANDISERS



HDM-13



HDM-26



## COUNTERTOP HEATED DISPLAY MERCHANDISERS

These merchandisers feature passive humidity control with a removable water tray.

- ◆ Removable water pan to add and control humidity
- ◆ Three (3) adjustable shelves inside, top of unit also functional as a shelf
- ◆ Lighted front display for branding visuals
- ◆ Visible thermometer gauge to ensure food keeps at proper temperatures
- ◆ Adjustable thermostat from 85°F to 195°F (30°C to 90°C)
- ◆ Customer-facing front service and rear access doors

| ITEM   | OVERALL DIMENSIONS<br>L" X D" X H" (mm)             | POWER                      | PLUG       | SHIP<br>WEIGHT       |
|--------|---|----------------------------|------------|----------------------|
| HDM-13 | 13-11/16" x 19-9/16" x 26-1/8"<br>(347 x 495 x 663) | 110-120V~60Hz, 800W, 7.6A  | NEMA 5-15P | 50.7 lbs<br>(23 kgs) |
| HDM-26 | 26-11/16" x 19-9/16" x 26-1/8"<br>(677 x 495 x 663) | 110-120V~60Hz, 1000W, 9.5A |            | 79.4 lbs<br>(36 kgs) |

| ITEM   | DESCRIPTION | UOM | CASE |
|--------|-------------|-----|------|
| HDM-13 | 13-1/2"L    | Set | 1    |
| HDM-26 | 26-1/2"L    | Set | 1    |



Control Panel

## REFRIGERATED COLD BEVERAGE DISPLAY

Fits up to 100 cans



CRD-1



CRD-1K



CRD-Series uses environmentally friendly R290 refrigerant

## COUNTERTOP REFRIGERATED BEVERAGE DISPLAYS

With its clear panels and 4 LED light strips, this countertop display can keep up to 100 standard 12 oz cans chilled. These units use R290 refrigerant making them an environmentally-responsible choice.

- ◆ Digital temperature display from 32°F to 42°F (0°C - 6°C)
- ◆ R-290 environmentally safe refrigerant
- ◆ 360° view of refrigerated product
- ◆ 2 double, curved-glass doors for dual access and easy placement of inner contents
- ◆ 4 LED strips for effective product lighting
- ◆ Comfortably fits up to 100 cans (standard 12 oz) with 25 cans per shelf
- ◆ 4-level merchandising display; three (3) shelves are adjustable to fit multiple product heights
- ◆ Automatic defrost and ventilated cooling system

| OVERALL DIMENSIONS<br>L" X D" X H" (mm)         | POWER                     | PLUG       | SHIP<br>WEIGHT        |
|---|---------------------------|------------|-----------------------|
| 16 3/4" x 16 15/16" x 38 1/2" (425 x 429 x 978) | 110-120V~60Hz, 230W, 2.7A | NEMA 5-15P | 85.89 lbs<br>(39 kgs) |
| SHELF DIMENSIONS L" X D" (mm)                   |                           |            |                       |
| 14-3/8" x 12-1/8" (365 x 307)                   |                           |            |                       |

| ITEM   | DESCRIPTION | UOM | CASE |
|--------|-------------|-----|------|
| CRD-1  | White       | Set | 1    |
| CRD-1K | Black       | Set | 1    |

### IMPORTANT

This unit is intended for use in commercial food-service operations, for the cooling and display of sealed food and beverage only.