

PROJECT:		
ITEM #		OTY:
MODEL #		
ΔΙΔ #	SIS #	

WORKTOP FREEZER WITH DRAWERS

VWFD32HC-2



EXCLUSIVE WARRANTY

- 7 Year Parts, Labor and Compressor
- Exclusive 2 Year Warranty On Magnetic Door Gaskets
- Lifetime Warranty On Handles & Hinges (parts only)



Refrigeration System Uses R-290 Refrigerant To Comply

Adaptive Defrost For Reduced Energy Consumption And

Freezer Capable Of Maintaining Product Temperature -10°F



CABINET CONSTRUCTION

- Stainless Steel Exterior (galvanized back & bottom)
- Aluminum Interior
- Stainless Steel 20 Gauge Drawers
- 4" High, Foamed-In-Place Backsplash
- One Piece, Snap-In Magnetic Drawer Gaskets
- 6" Casters
- 8' Cord And Plug (see electrical data for details)

FEATURES

- Full Electronic Control
- Stay-Open Drawer Feature For Easy Product Loading
- Low Profile Horizontal Drawer Handles
- Heavy-Duty Pan Supports Provided
- Drawers Accommodates 6" Deep Full Size Food Service Pans In Both Upper And Lower Drawers (pans not included)
- Telescoping Drawer Slides With Locking Mechanism

Laser y

REFRIGERATION

.

With All Environmental Concerns

Epoxy Coated Evaporator Coil

Rear Mounted Refrigeration System

More Consistent Product Temperatures

Please Verify Qualifying Units By Visiting: www.energystar.gov/cfs

OPTIONS & ACCESSORIES

- Stainless Steel Interior
- Stainless Steel Back

• Cutting Board

• 6" Legs Or 6" Seismic Legs

Drawer Locks

- Casters: 3", Roller Kit, Low Profile
- Remote Models* (6" legs only) (refrigerant must be specified at time of order, see note on back on page)

3779 Champion Blvd, Winston-Salem, NC 27105

ph: (888) 845-9800 fax: (800) 253-5168


Sales@VictoryRefrigeration.com VictoryRefrigeration.com


APPROVAL: _


VICTORY WORKTOP FREEZER WITH DRAWERS

VWFD32HC-2









Drawer Configurations



We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM)

3" Bottom	& 2'	' Rear	clearance	is	required
-----------	------	--------	-----------	----	----------

CHARACTERISTICS		ELECTRICAL DATA		SHIPPING DETAILS		
Net Capacity (cubic ft.)	7.22	Cabinet Voltage	115/60/1	Height	40″	
Width, Overall (in.)	32″	Total Amperes	4.0	Width	33″	
Depth, Overall (with handle)	32 5/8″	NEMA Plug (8' cord)	5-15P	Depth	33″	
Height Overall (6" casters)	39 1/2"	REFRIGERATION DATA		Crated Weight	235 lbs	
Depth, Drawer Open (in.)	48 11/16″	Condensing Unit Size, HP	1/3	*NOTE: Remote units are field wired and comes with 6" legs. Refrigerant must be specified		
Drawer Openings (in.)	27 9/16" x 7 5/8" 27 9/16" x 11 1/8"	Refrigerant*	R-290			
No. Of Drawers	2	Capacity (BTU/HR) (100°F/-20°F)	1865			
		Heat Rejection (BTU/HR)	2797.5	at time of order.		
		Charge (lbs/grams/ounces)	0.165 / 75 / 2.64			

3779 Champion Blvd, Winston-Salem, NC 27105 ph: (888) 845-9800 fax: (800) 253-5168

Sales@VictoryRefrigeration.com VictoryRefrigeration.com

Rev. 7/18/24 Printed in U.S.A.

