

GARLAND®

Master Series Heavy-Duty Range-Match Briquette Broiler With Flame-Failure Protection

Project _____
Item _____
Quantity _____
CSI Section 11400
Approved _____
Date _____

Models

- MST17B
- MST17BT
- MST17BE
- MST24B
- MST24BT
- MST24BE
- MST34B
- MST34BT
- MST34BE



Model MST24BE
Shown with Optional Backguard

Standard Features

- Stainless steel front doors
- Stainless steel front and sides
- Stainless steel front rail
- 1-1/4" NPT front manifold
- Dual-sided, cast-iron broiler grates with 1/2" (13mm) rounded bar, (board brand) and diamond (fine) pattern on opposite sides
- 15,000 BTU (4.39 kW) burners
- Heavy-weight, long-lasting ceramic briquettes
- Piezo spark ignition with constant burning pilots
- Storage base interior of aluminized steel
- Modular top broilers (suffix "BT"), modular broiler is 14-1/2" (368mm) from broiler base to working height
- 6" (152mm) chromed steel adjustable legs
- Electric Spark ignition on all pilots
Suffix -E models
- Flame-failure protection for all burners

Options & Accessories

- Stainless steel main back
- Rear gas connection; 3/4" NPT
- Gas regulator 3/4" or 1-1/4"
- Gas shut off valve; 3/4", 1" or 1-1/4" NPT
- Gas flex hose & quick disconnect (3/4", 1" or 1-1/4" NPT x 5') w/ restraining device, please specify
- End caps and cover (NC, specify)
- Stainless steel backguard: 10" (354mm), 17" (432mm) or 33" (838mm)
- Dual-sided, steel diamond, (fine) in lieu of cast-iron grate
- Dais base
- Polyurethane non-marking swivel casters (4) w/front brakes
- 6" (152mm) stainless steel adjustable legs
- 230 volt, 50 cycle components, electric ignition, (export)

Specifications

Master Series briquette broiler with stainless steel front and sides.

Broiling area consists of heavy-duty rack sections which are easily moved for flat or tilt position broiling.

Dual-sided, cast-iron broiler grates with 1/2" (13mm) rounded bar, (board brand) and diamond (fine) pattern on opposite side.

15,000 BTU (4.39 kW) burners controlled by individual Hi-Lo valves.

Heavy-weight, long-lasting briquettes.

Flame-failure protection for all burners

Large capacity full-length grease drawers.

Heavy-weight, long-lasting briquettes.

Cabinet, 17" (432mm), 24" (610mm), or 34" (864mm), wide by 34" (869mm) deep, with two stainless steel full-sized hinged doors and front.

Natural gas or propane.

Available in modular models, suffix BT.

NOTE: Broilers supplied with casters must be installed with an approved restraining device.

NOTE: All Master Series ranges, attachments, fryers, and broilers require a high shelf or backguard flue attachment - sold separately.



Master Series Heavy-Duty Range-Match Briquette Broiler
With Flame-Failure Protection


Garland Commercial Ranges Ltd.
1177 Kamato Road,
Mississauga, Ontario
L4W 1X4 CANADA

General Inquires 1-905-624-0260
USA Sales, Parts and Service 1-800-424-2411
Canadian Sales 1-888-442-7526
Canada or USA Parts/Service 1-800-427-6668

www.garland-group.com
8164D
11/25



Master Series Heavy-Duty Range-Match Briquette Broiler With Flame-Failure Protection



Input Specifications	MST17B/BT	MST24B/BT	MST34B/BT
Input	45,000 BTU (13.2 kW)	60,000 BTU (17.6 kW)	90,000 BTU (26.4 kW)
Inlet/Manifold Size	1-1/4" NPT	1-1/4" NPT	1-1/4" NPT

Installation Notes		
Installation Clearances ¹	Entry Clearances	Operating Pressure
Clearance: 0" for Installation in Non-Combustible Surroundings Only	Crated: 39-1/4" (997mm) Uncrated: 34-1/4" (870)	Natural: 6" WC (15mbar) Propane: 10" WC (25mbar)

Product	Width: In(mm)	Depth: In(mm)	Shipping	
			Cu Ft	Shipping Wt: (Lb/Kg)
MST17B	17(432)	38(965)	24	235/107
MST17BT	17(432)	38(965)	10	135/60
MST24B	24(612)	38(965)	30	330/150
MST24BT	24(612)	38(965)	16	230/105
MST34B	34(864)	38(965)	48	510/231
MST34BT	34(864)	38(965)	24	390/180

¹NOTE: Installation clearance reductions are applicable only where local codes permit.

Electrical characteristics for models with Suffix - E: 120VAC single phase 60 Hz, 1 amp 6 ft. (1.8m) NEMA 5-15P cord and plug provided. 230VAC export direct connect single phase 50 Hz, 1 amp.

Garland/U.S. Range products are not approved or authorized for home or residential use, but are intended for commercial applications only. Garland / U.S. Range will not provide service, warranty, maintenance or support of any kind other than in commercial applications.

Garland reserves the right to make changes to the design or specifications without prior notice.

Garland Commercial Ranges Ltd.
1177 Kamato Road,
Mississauga, Ontario
L4W 1X4 CANADA

General Inquires 1-905-624-0260
USA Sales, Parts and Service 1-800-424-2411
Canadian Sales 1-888-442-7526
Canada or USA Parts/Service 1-800-427-6668

www.garland-group.com
8164D
11/25

