

PROJECT:		
ITEM #		OTY:
MODEL #		
AIA#	SIS #	

# SHALLOW DEPTH GLASS HALF-DOOR REACH-IN FREEZER

FSA-2N-S1-HG-HC



# **EXCLUSIVE WARRANTY**

- 7 Year Parts, Labor and Compressor
- Exclusive 2 Year Warranty On Magnetic Door Gaskets
- Lifetime Warranty On Handles & Hinges (parts only)







### CABINET CONSTRUCTION

- · Stainless Steel Exterior
- **Aluminum Interior**
- · Stay-Open Door Feature For Easy Product Loading
- · Glass Half-Door
- · LED On/Off Selection Within Controller
- · Heavy-Duty Cylinder Locks
- One Piece, Snap-In Magnetic Door Gaskets
- Low Profile Vertical Door Handles
- · Hinged Front Shroud
- · Energy Saving Thermal Breaker
- · Stainless Steel Breaker Caps
- · 6 Silver Freeze Wire Shelves
- 6" High Adjustable Stainless Steel Legs
- · 8' Cord And Plug (see electrical data for details)

#### **FEATURES**

- · Full Electronic Control With Touchpoint Interface
- · Expansion Valve Technology
- · Manager's Lockout Feature
- Anti-Condensate Perimeter Heater
- Variable Speed Compressor Technology

#### REFRIGERATION

- Refrigeration System Uses R-290 Refrigerant To Comply With All **Environmental Concerns**
- Hot Gas Condensate Evaporator
- · Adaptive Defrost For Reduced Energy Consumption And More **Consistent Product Temperatures**
- · Epoxy Coated Evaporator Coil, Located Out Of The Food Zone
- Freezer Capable Of Maintaining Product Temperature -10°F



Please Verify Qualifying Units By Visiting: www.energystar.gov/cfs

## **OPTIONS & ACCESSORIES**

- · Stainless Steel Case Back
- · Stainless Steel Kick Plate
- Door Swing Orientation (at time of order) 3", 6" Casters Or 6" Seismic Legs
- · Additional Shelves

Rev. 7/1/24 Printed in U.S.A.


- · Heat Shield (left, right)
- Tray Slides (type A & A/C)
- Ultra Glass Half-Door (as shown above)
- FlexTemp Models Maintain Between 28°F And 38°F
- Remote Models\* (6" legs only) (refrigerant must be specified at time of order,


3779 Champion Blvd, Winston-Salem, NC 27105				
ph: (888) 845-9800   fax: (800) 2	53-5168			
Sales@VictoryRefrigeration.com	VictoryRefrigeration.com			


ΛΡΡΡΩ\/ΛΙ ·	DATE:











We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM)

### 12" Top clearance is required

CHARACTERISTICS ELECTRICAL DATA			SHIPPING DETAILS		
Net Capacity (cubic ft.)	41.35	Cabinet Voltage	115/60/1	Height	88"
Width, Overall (in.)	58 2/5"	Total Amperes	13.9	Width	66"
Depth, Overall (with handle)	28 9/10"	NEMA Plug (8' cord)	5-15P	Depth	41"
Height Overall (6" legs)	84 1/5"	REFRIGERATION DATA		Crated Weight	580 lbs
Depth, Door Open 90°	53 4/5"	Condensing Unit Size, HP	3/4	*NOTE: Remote units are field wired and comes with 6" legs. Refrigerant must be specified	
Door Openings (in.)	23" x 25 1/4"	Refrigerant*	R-290		
No. Of Doors/Shelves	4/6	Capacity (BTU/HR) (100°F/-20°F)	4900		
		Heat Rejection (BTU/HR)	7350	at time of order.	
		Charge (lbs/grams/ounces)	0.2866 / 130 / 4.59		

3779 Champion Blvd, Winston-Salem, NC 27105 | ph: (888) 845-9800 | fax: (800) 253-5168

Sales@VictoryRefrigeration.com VictoryRefrigeration.com

Rev. 7/1/24 Printed in U.S.A.

