

## RELIABLE SPACE... ECONOMICALLY.

OlympicShelving.com

## WIRE SHELVING —— CHROMATE

- Unique Design: The open wire design of these carbon-steel shelves minimizes dust accumulation and allows a free circulation of air, greater visibility of stored items and greater light penetration.
- Versatile Construction: Wire shelving can change as quickly as your needs change.
- Fast, Secure Assembly: Posts have circular grooves at 1" (25mm) intervals. A tapered split sleeve snaps together around each post. Tapered openings in the shelf corners slide over the tapered split sleeves providing a positive lock. Shelf is assembled in minutes without the use of any special tools.
- **Shelf Wires:** Run front to back, allowing you to slide items on and off shelves smoothly.
- Shelf Accessibility: Shelves can be loaded/unloaded easily from all sides. This open construction allows use of maximum storage space of cube.
- Adjustability: Shelves can be adjusted at
   1" (25mm) intervals along the entire length of the post.
- Finish: Chromate finish
- Posts: Bolt levelers compensate for surface irregularities on stationary posts.








## **WIRE SHELVES**

Width/Length		Approx. Weigh (lbs.)		Pack Quantity	Cat. No. Chromate
(in.)	(mm) 355 x 610	5.1	(kg) 2.3	4	J1424C
14 x 30	355 x 760	6.0	2.7	4	J1430C
14 x 36	355 x 914	6.8	3.1	4	J1436C
14 x 42	355 x 1066	8.0	3.6	4	J1442C
14 x 48	355 x 1219	10.2	4.6	4	J1448C
14 x 60	355 x 1524	13.2	6.0	2	J1460C
14 x 72	355 x 1829	15.5	7.0	2	J1472C
18 x 24	457 x 610	5.6	2.5	4	J1824C
18 x 30	457 x 760	6.7	3.0	4	J1830C
18 x 36	457 x 914	7.8	3.5	4	J1836C
18 x 42	457 x 1066	8.8	4.0	4	J1842C
18 x 48	457 x 1219	9.8	4.4	4	J1848C
18 x 54	457 x 1370	11.8	5.4	2	J1854C
18 x 60	457 x 1524	13.6	6.2	2	J1860C
18 x 72	457 x 1829	16.7	7.6	2	J1872C
21 x 24	530 x 610	6.6	3.0	4	J2124C
21 x 30	530 x 760	8.0	3.6	4	J2130C
21 x 36	530 x 914	9.0	4.1	4	J2136C
21 x 42	530 x 1066	10.2	4.6	4	J2142C
21 x 48	530 x 1219	13.0	5.9	4	J2148C
21 x 54	530 x 1370	14.1	6.4	2	J2154C
21 x 60	530 x 1524	15.3	6.9	2	J2160C
21 x 72	530 x1829	18.0	8.2	2	J2172C
24 x 24	610 x 610	7.4	3.4	4	J2424C
24 x 30	610 x 760	9.3	4.2	4	J2430C
24 x 36	610 x 914	10.3	4.7	4	J2436C
24 x 42	610 x 1066	11.6	5.3	4	J2442C
24 x 48	610 x 1219	13.1	5.9	4	J2448C
24 x 54	610 x 1370	15.0	6.8	2	J2454C
24 x 60	610 x 1524	17.0	7.7	2	J2460C
24 x 72	610 x 1829	20.6	9.3	2	J2472C

Up to  $48^{\circ}$  (1220mm) Length = 800 lbs. (363kg), evenly distributed.  $54^{\circ}$ - $72^{\circ}$  (1829mm) Length = 600 lbs. (272kg), evenly distributed.



## POSTS — 1 PIECE

Pack Quantity	Cat. No. Stationary Post Chromate	Height* Stationary Post (in.) (mm)		Approx. Weight Per Post (lbs.) (kg)		Cat. No. Mobile Post Chromate	Height** Mobile Post (in.) (mm)		Approx. Weight Per Post (lbs.) (kg)	
4	J7C	71/2	191	0.5	0.2	J7UC	6¾	171	0.4	0.2
4	J13C	14½	370	0.9	0.4	J13UC	13¾	349	0.8	0.4
4	J33C	341/2	875	1.7	0.8	J33UC	34¾	857	1.5	0.7
4	J54C	54%	1385	2.5	1.1	J54UC	5313/16	1366	2.3	1.0
4	J63C	62%	1590	3.0	1.4	J63UC	6113/16	1570	2.8	1.3
4	J74C	74%	1895	3.6	1.6	J74UC	73%	1873	3.4	1.5
4	J86C	86%	2200	4.1	1.9	J86UC	85%	2181	3.9	1.8





Split Sleeves



Posts are grooved at 1" (25mm) increments and numbered at 2" (50mm) increments. Posts are double-grooved every 8" (203mm) for easy identification.



Information and specifications are subject to change without notice. Please confirm at the time of order.

<sup>\*\*</sup>Height includes leveling bolt and cap.
\*\*Mobile posts come without leveling bolt assembly and accommodate stem casters.

<sup>\*\*</sup>Height is for post only.