



	SM-13F	SM-23R SM-23F	SM-45R SM-45F	SM-45RS	SM-52R SM-72F
Door	1	1	2	2	3
Shelves	4	4	8	8	12
Exterior Dimensions (L x D x H)	27 ³ / ₈ x 27 ¹ / ₂ x 80 ³ / ₈	28 ³ / ₈ x 31 ⁷ / ₈ x 79 ³ / ₈ 31 ¹ / ₈ x 31 ¹ / ₄ x 80 ³ / ₄	53 ¹ / ₈ x 32 x 79 ³ / ₈ 53 ¹ / ₈ x 31 ⁷ / ₈ x 79 ³ / ₈	53 ¹ / ₈ x 31 ⁷ / ₈ x 79 ³ / ₈	78 ¹ / ₄ x 29 ⁷ / ₈ x 80 ⁷ / ₈ 79 ¹ / ₂ x 30 ⁵ / ₈ x 80 ³ / ₄
Capacity cu.ft.	13	23	45	45	63
HP	3/4	1/3 3/4	3/4 1 1/4	1/2	3/4 + (2) 3/4 +
Voltage	115/60/1	115/60/1	115/60/1	115/60/1	115/60/1
Amps	10.5	8.6 9.6	9.2 14.4	9.2	14.5 20.5
Nema Config	5-15P	5-15P	5-15P 5-20P	5-15P	5-20P
Crated/Uncrated Weight	374/330 lb	337/284 lb 550/506 lb	561/440 lb 660/572 lb	495/440 lb	814/715 lb 858/770 lb

- Bottom mount condensing unit
- Rounded corner design for easy cleaning of inside storage
- Double and/or triple pane thermal insulated glass door with aluminum frames
- Refrigeration system holds 33°F to 41°F (0.5°C to 5°C) or -10°F to 0°F (-23°C to -18°C) for optimum food preservation
- Electronic control system: Adjustable temperature set point and defrost frequency as well as error codes to diagnose service issues
- Adjustable, heavy duty PVC coated shelves
- Standard heavy duty casters make it easy to move and clean underneath
- LED lighting: Visibility of products, last longer and consume low energy
- Lighted to panel: Lighted panel above the cabinet making the merchandiser more eye-catching

* Specifications subject to change without notice.

