


## Cupcake Pans Aluminized steel (unless otherwise noted)

Item #	In Stock	Coating	Description	Arrangement	Vol. (oz)*	Mould Dimensions (in)			Centers (in)		Weight Each (lb)	Overall Size (in)
						Top (A)	Btm. Out. (B)	Depth (C)	L	W		
45125		Glazed	26 gauge cups, 22 gauge corrugated panel, curled rim	3 rows of 4	3.8	2 <sup>3</sup> / <sub>4</sub>	2 <sup>1</sup> / <sub>16</sub>	1 <sup>3</sup> / <sub>8</sub>	3 <sup>5</sup> / <sub>16</sub>	3 <sup>5</sup> / <sub>16</sub>	2.3	11 <sup>1</sup> / <sub>8</sub> x 15 <sup>3</sup> / <sub>4</sub>
45225		Glazed	26 gauge, wire in rim	3 rows of 4	3.8	2 <sup>3</sup> / <sub>4</sub>	2 <sup>1</sup> / <sub>16</sub>	1 <sup>3</sup> / <sub>8</sub>	4	4	3.8	12 <sup>7</sup> / <sub>8</sub> x 17 <sup>7</sup> / <sub>8</sub>
45525		Glazed	26 gauge, square corners, wire in rim	4 rows of 6	3.8	2 <sup>3</sup> / <sub>4</sub>	2 <sup>1</sup> / <sub>16</sub>	1 <sup>3</sup> / <sub>8</sub>	3 <sup>5</sup> / <sub>16</sub>	3 <sup>5</sup> / <sub>16</sub>	5.2	14 <sup>1</sup> / <sub>16</sub> x 20 <sup>11</sup> / <sub>16</sub>
45575		Glazed	26 gauge, wire in rim	5 rows of 7	3.8	2 <sup>3</sup> / <sub>4</sub>	2 <sup>1</sup> / <sub>16</sub>	1 <sup>3</sup> / <sub>8</sub>	3 <sup>5</sup> / <sub>16</sub>	3 <sup>5</sup> / <sub>16</sub>	7.3	17 <sup>7</sup> / <sub>8</sub> x 25 <sup>7</sup> / <sub>8</sub>
45605		Glazed	26 gauge, wire in rim	4 rows of 6	3.8	2 <sup>3</sup> / <sub>4</sub>	2 <sup>1</sup> / <sub>16</sub>	1 <sup>3</sup> / <sub>8</sub>	4	4	6.5	17 <sup>7</sup> / <sub>8</sub> x 25 <sup>7</sup> / <sub>8</sub>
46120		Plain	20 gauge aluminum, square corners, wire in rim	3 rows of 4	3.8	2 <sup>3</sup> / <sub>4</sub>	2 <sup>1</sup> / <sub>16</sub>	1 <sup>3</sup> / <sub>8</sub>	3 <sup>5</sup> / <sub>16</sub>	3 <sup>5</sup> / <sub>16</sub>	2.0	10 <sup>3</sup> / <sub>4</sub> x 14 <sup>1</sup> / <sub>8</sub>
46125		Glazed	20 gauge aluminum, square corners, wire in rim	3 rows of 4	3.8	2 <sup>3</sup> / <sub>4</sub>	2 <sup>1</sup> / <sub>16</sub>	1 <sup>3</sup> / <sub>8</sub>	3 <sup>5</sup> / <sub>16</sub>	3 <sup>5</sup> / <sub>16</sub>	2.0	10 <sup>3</sup> / <sub>4</sub> x 14 <sup>1</sup> / <sub>8</sub>
46520		Plain	20 gauge aluminum, square corners, wire in rim	4 rows of 6	3.8	2 <sup>3</sup> / <sub>4</sub>	2 <sup>1</sup> / <sub>16</sub>	1 <sup>3</sup> / <sub>8</sub>	3 <sup>5</sup> / <sub>16</sub>	3 <sup>5</sup> / <sub>16</sub>	3.5	14 <sup>1</sup> / <sub>8</sub> x 20 <sup>3</sup> / <sub>4</sub>
46525		Glazed	20 gauge aluminum, square corners, wire in rim	4 rows of 6	3.8	2 <sup>3</sup> / <sub>4</sub>	2 <sup>1</sup> / <sub>16</sub>	1 <sup>3</sup> / <sub>8</sub>	3 <sup>5</sup> / <sub>16</sub>	3 <sup>5</sup> / <sub>16</sub>	3.5	14 <sup>1</sup> / <sub>8</sub> x 20 <sup>3</sup> / <sub>4</sub>



\*Volume (Vol.) indicates liquid volume of mould when filled to brim. Use 60-70% to estimate actual batter weight.

