



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CUP-11G1/1 C CI 230V 1N 50Hz

19097885

05/05/2023

EU Model shown – UK models have castors as standard

DENOMINATION:

Refrigerated cabinet - Concept Gastronorm 1/1, at 50Hz.

DESCRIPTION :

- Structure built with AISI-304 stainless steel.
 - 60 mm, 40 kg/m³ injected polyurethane insulation.
 - Storage trays at 23 different levels 55 mm from each other.
 - Forced draught system with cooling unit outside the room and monoblock system to optimise storage capacity.
 - Copper piping and aluminium flaps evaporator.
 - Digital display for electronic and digital control of temperature and defrosting.
 - Opened door delay alarm.
 - Self-closing and stay open doors. When opened less than 90° they close by themselves. When opened more than 135° they stay open.
 - Built-in drainage to get rid of waste liquids inside the unit.
 - Embedded bottom and curved panels inside for easy cleaning and maintenance.
 - Height adjustable stainless steel legs.
 - Working temperature: from 0 °C to +8 °C (refrigerators) and from -18 °C to -22 °C (freezers).
 - Tested in climatic class 4.
 - LED interior lighting and power switch.
- Refrigerated cabinet

POSSIBLE OPTIONS :

- Stainless Backing
- Legs instead of castors
- Door frame resistance
- Glass door
- Locks
- Opposite Opening
- Pedal
- Remote group


POSSIBLE ACCESSORIES :

- REFRIGERATION
- ACCESSORIES
- GASTRONORM GRIDS

SUPPLIED ACCESSORIES:

- 12035781 GN 1/1 grid in epoxy (530x325) 3

DIMENSIONS



X Width	490 mm	X Gross width	770 mm
Y Depth	700 mm	Y Gross depth	565 mm
Z Height	2010 mm	Z Gross height	2100 mm
Net Weight	102,0 kg	Gross Weight	115,0 kg
Net volume	1,122 m ³	Gross volume	0,914 m ³

ELECTRICITY TECHNICAL SPECIFICATIONS

Amperage (A)	1 A
Electric frequency	50Hz
Electric power	0,205 kW
Voltage	230V - 1N

GAS TECHNICAL SPECIFICATIONS

Gas type	R-600a
----------	--------

COLD TECHNICAL SPECIFICATIONS

Annual elec. consumption	726,00 kWh
Clasif. Energy efficiency	D
Climate class	4
Cooling gas load	100,000 g
Energy Efficiency Index	73,48 %
Model Type	Vertical cabinet
Power consumption 24h	1,99 kWh
Refrigeration net.vol	231 L
Refrigeration power	0,361 kW

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1+T-2A
--------------------------	----------

OTHERS

Condensation system	Vent.
Number of doors	1





Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CUP-11G1/1 C CI 230V 1N 50Hz

19097885

05/05/2023

EU Model shown – UK models have castors as standard

