

**Digital Undercounter  
 ecostore HP Refrigerated Counter - 2  
 Door (R290) with top and wheels, UK  
 plug**


ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_


**710448 (EJ2HBAAXXG)**

2-door Refrigerated Counter, -2+10°C (R290), with wheels - UK

### Short Form Specification

**Item No.** \_\_\_\_\_

Internal and external doors, front and side panels in 304 AISI stainless steel. N.2 doors. With top. Built-in refrigeration unit. Ventilated. Refrigerant R290. High-density expanded polyurethane foam, 90 mm in thickness, with cyclopentane injection. Digital control panel. Completely automatic defrosting and automatic evaporation of defrost water obtained by hot gas. Temperature range: -2+10°C. CFC and HCFC free. Feet in 304 AISI stainless steel, adjustable in height. Delivered with wheels and with UK plug.

**APPROVAL:** \_\_\_\_\_

### Main Features

- Tropicalized unit (43°C ambient temperature).
- This appliance is intended for use in ambient temperatures up to 40°C.
- Digital control panel allowing the easy and precise setting and control of the internal temperature.
- Operating temperature can be adjusted from -2 to +10 °C to suit different food storage requirements.
- Complies with main international certification bodies and is CE marked.
- Kit 1/2 drawers available as accessory.
- The door self-closes when opened less than at a 90° angle and is equipped with a door seal to guarantee perfect closure.
- Completely automatic defrosting and automatic evaporation of defrost water by hot gas.
- Forced air cooling system guaranteeing great uniformity of the temperature in the counter and excellent conservation of the food quality.
- High standards of hygiene and ease of cleaning are guaranteed by the rounded internal corners of the cabinet and easily removable runners and grids.
- Kit 1/3 drawers available as accessory.
- Connectivity ready for real time access to connected appliances from remote and data monitoring (requires optional accessory).

### Construction

- External back panel in galvanized steel.
- Built-in compressor to suit operating conditions.
- CFC and HCFC free.
- Internal and external structure, bottom, doors, front and side panels, base and 50mm thick removable worktop in stainless steel.

### Included Accessories

- 2 of Kit 1/1 grey rilsan grid and 2 side runners for refrigerated counters PNC 881109

### Optional Accessories

- Kit integrated HACCP for digital refrigerators (IR33)  PNC 880252
- 1/1GN grey rilsan grid for refrigerated counters  PNC 881107
- 2 side runners for 1/1 GN ecostore refrigerated counters  PNC 881108
- Kit 1/1 grey rilsan grid and 2 side runners for refrigerated counters  PNC 881109
- 1/1 GN plastic container, H=65 mm  PNC 881110
- 1/1 GN plastic container, H=100 mm  PNC 881111
- 2x½ drawer kit for refrigerated counters - h650mm  PNC 881176
- 3x1/3 drawer kit for refrigerated counters - h650mm (only for refrigerated counters)  PNC 881177



**Electrolux**  
PROFESSIONAL

**Digital Undercounter  
ecostore HP Refrigerated Counter - 2  
Door (R290) with top and wheels, UK plug**


- 1/3 and 2/3 bottle drawer kit for refrigerated counters - h650mm (only for refrigerated counters) PNC 881178
- Kit 4 wheels, H=100 mm (2 with brakes) for refrigerated counters PNC 881191
- Kit 4 wheels, H=150 mm (2 with brakes) for 2&3 compartment refrigerated counters PNC 881193
- Lock for refrigerated counters with two compartments - h650mm PNC 881245




**Digital Undercounter  
ecostore HP Refrigerated Counter - 2 Door (R290) with top and wheels,  
UK plug**  
The company reserves the right to make modifications to the products  
without prior notice. All information correct at time of printing.

2020.11.26

Front




Side



EI = Electrical inlet (power)

Top


**Electric**

Supply voltage:  
 710448 (EJ2HBAAXXG) 220-240 V/1 ph/50 Hz  
 Electrical power max.: 0.22 kW

**Key Information:**


Gross capacity: 290 lt  
 Net Volume: 163.600006103516 lt  
 N° of doors:  
 External dimensions, Width: 1245 mm  
 External dimensions, Height: 850 mm  
 External dimensions, Depth: 700 mm  
 Internal Dimensions (depth): 560 mm  
 Internal Dimensions (height): 510 mm  
 Internal Dimensions (width): 798 mm  
 Net weight: 94 kg  
 Shipping volume: 1 m<sup>3</sup>  
 Depth with doors open: 1310 mm

**Refrigeration Data**

Control type: Digital  
 Compressor power: 1/4 hp  
 Refrigerant type: R290  
 GWP Index: 3  
 Refrigeration power: 320 W  
 Refrigerant weight: 50 g  
 Min/Max internal humidity: 40/85  
 Operating temperature min.: -2 °C  
 Operating temperature max.: 10 °C  
 Operating mode: Ventilated

**Product Information (EU Regulation 2015/1094)**

Energy Class: B  
 Yearly and daily energy consumption: 560kWh/year - 2kWh/24h  
 Climate class: Heavy Duty (5)  
 Energy Efficiency Index (EEI): 25,36



### EU energy labelling from 1st July 2016

The European energy labelling scheme for professional refrigerators and freezers is based on requirements setting Minimum Energy Performance standards for commercial refrigeration cabinets sold within the EU. These requirements are designed to drive energy efficiency and environmentally friendly approach for professionals. The European energy labelling scheme will apply to all manufacturers and importers who sell and market products within the EU and it is mandatory across Europe.

Important: all products which consume energy above the minimum level will not be able to be sold within the EU from 1 July 2016.