

6-BURNER GAS COOKER ON MAXI OVEN GAS

Project:
Rev.:
Zone:
Location:



CODICE
CR0995199

MODELLO
D96/10CGFLR

SERIE
DIAMANTE90



GENERAL CHARACTERISTICS

In addition to offering the maximum choice of solutions and 2 mm thick and 90 cm deep tops, this series has all the power, robustness and functionality you need to work efficiently. External coatings and feet in stainless steel with Scotch Brite finish. Working table height adjustable from 840 to 900 mm. Range modularity: 200-400-600-800-1200. Wide range of accessories.

TECHNICAL SPECIFICATIONS

Upper burners with stabilised flame, made of nickel-plated cast iron. Thermocouple safety valves with pilot flame.
Black acid-resistant enamelled cast iron grids with long spokes for holding small pans.
AISI304 stainless steel drip trays.
Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.
Nickel-plated cast-iron stabilised flame burners with double-crown spreader (improved performance facilitated by a flame distributed over two different sectors), Grid with long spokes to facilitate holding small pots and pans
90° venturi that prevents the nozzle from clogging and accumulating dirt.

Nickel-plated cast-iron stabilised flame burners with double-crown spreader (improved performance facilitated by a flame distributed over two different sectors), Grid with long spokes to facilitate holding small pots and pans

Removable AISI 304 stainless steel bowl for maximum hygiene.

For gas ovens, radiant plate in cast iron for even heat distribution even heat distribution, stainless steel for electric ovens. Insulated stainless steel door and inner door mounted on high-strength hinges.

Equipment certified for low voltage directive 2014/35/EU according to the international CB scheme.

Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.

6-BURNER GAS COOKER ON MAXI OVEN GAS

Project:
Rev:
Zone:
Location:



CODICE
CR0995199

MODELLO
D96/10CGFLR

SERIE
DIAMANTE90

Technical Information

SPECIFICATION	DATA
MATERIAL	CR0995199
DEFINITION	D96/10 CGFLR 6-BURNER OVEN MAX.GRILL EL
COMMERCIAL LINE	DIAMANTE
SUPPLY	MIXED
DIM. WIDTH	1200 mm
DIM. PRODUCTIVITY	900 mm
DIM. HEIGHT	870 mm
NET WEIGHT	212,000 Kg
VOLUME (net)	0,940
PACKAGE LENGTH	1240,000 mm
PACKAGE WIDTH	1020,000 mm
PACKAGING HEIGHT	1130,000 mm
PACKAGE VOLUME	1,430 m3
GROSS PACKING WEIGHT	235,000 Kg
STANDARD POWER SUPPLY	380-415V 2N
FREQUENCY	50-60 Hz
ELECTRICAL POWER	4,500 kW
GAS POWER	44,20
GAS POWER (G25.3/25mbar)	39,40
IP GRADE	IPX5
CERTIFIED MODEL	D96/10 CGFLR

6-BURNER GAS COOKER ON MAXI OVEN GAS

Project:
 Rev:
 Zone:
 Location:




CODICE
CR0995199

MODELLO
D96/10CGFLR



SERIE
DIAMANTE90

SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION - ESQUEMA DE INSTALACION - INSTALLATIESCHEMA - IINSTALLATIONSRIITNINGAR


MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm
 MESURES EN cm - MEDIDAS EN cm - MATEN IN cm



- (D) 96/10 CGFL
- (D) 96/10 CGFLP
- (D) 96/10 CGFL2P
- (D) 96/10 CGFLR *
- (D) 96/10 CGFLRP *
- (D) 96/10 CGFLR2P *



(D) 96/10 GFLR



Legenda - Legende - Key - Légende - Leyenda - Legenda

- G** Attacco arrivo gas - Gasanschluss - Gas connection
 Arrivée gaz - Union de gas - Gasaansluiting
EN 10226-1 R 1/2; EN ISO 228-1 G 1/2 (DK)
- E *** Pressacavo entrata linea elettrica - Stopfbuchse
 Electric cable stress relief - Presse étoupe de câble él
 Pisacable - Elektrische kabelwartel

6-BURNER GAS COOKER ON MAXI OVEN GAS

Project:
Rev:
Zone:
Location:



CODICE
CR0995199

MODELLO
D96/10CGFLR

SERIE
DIAMANTE90

Product's PLUS



For gas ovens, radiant plate in cast iron for even heat distribution even heat distribution, stainless steel for electric ovens. Insulated stainless steel door and inner door mounted on high-strength hinges.

Equipment certified for low voltage directive 2014/35/EU according to the international CB scheme.



90° venturi that prevents the nozzle from clogging and accumulating dirt.



Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.



Nickel-plated cast-iron stabilised flame burners with double-crown spreader (improved performance facilitated by a flame distributed over two different sectors), Grid with long spokes to facilitate holding small pots and pans



Removable AISI 304 stainless steel bowl for maximum hygiene.

6-BURNER GAS COOKER ON MAXI OVEN GAS

Project:
Rev:
Zone:
Location:



CODICE
CR0995199

MODELLO
D96/10CGFLR

SERIE
DIAMANTE90

ACCESSORIES

CODE	MODELLO	DESCRIZIONE
SUPBRUC	SUP BRUC	
MA97365000	GGN1/1	
MA97375000	GGN2/1	
MA97377000	BF9M-X	
MA97376900	TGN2/1	
MA97378000	BF9M-T	
CR1353839	CR1353839	
CR1353849	CR1353849	
CR0592809	ZF12	
CR0592830	ZG	
CR0592820	9ZL	
MA97432000	R	
MA97433000	RI	
CR0592869	PZM	
CR0593580	9PT	
CR0592879	KPA	
CR0592940	9CAT *	Water column for top equipment