



# DISHWASHER UX-50SB 400/50/3N DD

Rack size 500x500mm and door clearance 380 mm. Double-skinned construction.



WARE WASHING  
COMMERCIAL DISHWASHERS

1303266



## SALES DESCRIPTION

Sani-Control: guaranteed disinfection  
Embedded bodywork and easy-grip door: hygienic and ergonomic  
Double-walled body: insulation and energy efficiency  
Exclusive Hydroblade™ washing arms: maximum effectiveness.  
3-stage filtering system.

### Sani-Control guarantee

- ✓ GUARANTEED DISINFECTION in compliance with standard DIN 10534.
- ✓ THERMAL LOCK function: Ensures that rinsing will be carried out at the ideal temperature to disinfect the dishes.

### New recessed bodywork

- ✓ Ergonomic design with rounded corners to prevent the accumulation of dirt and facilitate cleaning.
- ✓ Compact tank volume (50% water saving compared to the previous range).
- ✓ Embedded basket guides

### Double-Walled (Ultra ISO)

- ✓ Double-Walled Structure: thermo-acoustic insulation to attenuate the sound level and improve energy efficiency

### Hydroblade™ washing arms

- ✓ Redesigned nozzles for greater washing performance.
- ✓ The “monoblock” design delivers durability and resistance to impacts.
- ✓ 30% savings in water consumption during rinsing compared to the previous range.

### 3-stage filter system: surface, tank and extraction

- ✓ Keeps the washing water in optimal conditions to maintain constant washing performance.
- ✓ The surface filters feature an “easy-on” design and can be quickly removed without having to disconnect the washing arms.

### “Easy grip” door: new design with integrated door handle

- ✓ The integration of the components provides greater resistance and robustness.
- ✓ Designed to have no corners or areas that are difficult to access: prevents deposits of dirt and facilitates cleaning.
- ✓ Its ergonomic handle provides a perfect grip, even with wet hands.
- ✓ Double-walled door with safety microswitch and high quality seal
- ✓ 38 cm loading capacity: high versatility for washing a wide range of items: dishes, Euronorm trays, GN 1/1 tubs and pizza plates diam 39.

### Premium warewashing

- ✓ Ultra Xperience: high performance, without complications.
- ✓ Soft start: progressive start-up of the washing pump to protect fragile items.
- ✓ Colour LCD Display: intuitive communication of the machine status by means of messages, colour codes and icons.
- ✓ Dedicated cycles: selection of the ideal washing programme using icons.
- ✓ Adaptable: allows the main parameters of the machine to be adjusted to the needs of each user.
- ✓ TEMPERATURE DISPLAY
- ✓ Wash Plus+ function: increases the intensity of the wash cycle for greater cleaning performance
- ✓ Control panel with IP65 humidity protection.

### You will never WASH ALONE

- ✓ Tech-Services: our team of technicians will help you so that your machine is always ready for use.
- ✓ Design Services: tell us what your needs are and we will advise you.
- ✓ 60 years of experience and know-how at your disposal.

## INCLUDES

- ✓ Detergent Dispenser.
- ✓ 1 mixed basket (plates).
- ✓ 1 glasses basket.
- ✓ 1 small basket for cutlery.

## ACCESSORIES

- Stands for glass- and dishwashers
- Inserts & supplements
- Manual water softeners
- High Feet Kit
- Automatic water softeners
- Reverse Osmosis device OS-140P
- 500 x 500 mm. baskets



**www.sammic.co.uk**  
**Food Service Equipment Manufacturer**  
 Unit 2, Trevanah Road  
 Troon Industrial Park  
 LE4 9LS - Leicester  
**uksales@sammic.com**  
**Tel.: +44 0116 246 1900**



Project	Date
Item	Qty
Approved	

product sheet  
updated 01/10/2021



# DISHWASHER UX-50SB 400/50/3N DD

Rack size 500x500mm and door clearance 380 mm. Double-skinned construction.



1303266

## SPECIFICATIONS

Basket dimensions: 500 mm x 500 mm  
Maximum glass height: 380 mm

Cycle duration: -- " / -- " / -- "  
Production baskets/hour: -- / -- / --

Wash temperature: -- °C - 65 °C  
Rinse temperature: 65 °C - 87 °C

Boiler capacity: 8 l  
Wash tank capacity: 14 l

### Consumption and savings

Water consumption/cycle: 2.5 l  
Automatic saving mode in: y '  
Automatic switch-off: -- '

### Loading

Pump: -- W / -- Hp  
Tank: 1800 W  
Boiler: -- W  
Total loading: 5750 / 4550 / 2750 W (multi-power)


Electrical supply: 400 V / 50 Hz / 3N ~ (8.5 A)

### External dimensions (WxDxH)

- ✓ Width: 600 mm
  - ✓ Depth: 635 mm
  - ✓ Height: 835 mm
- Net weight: 64 Kg  
Noise level (1m.): -- dB(A)

### Crated dimensions

640 x 695 x 960 mm  
Gross weight: 71 Kg.



WARE WASHING  
COMMERCIAL DISHWASHERS



[www.sammic.co.uk](http://www.sammic.co.uk)

Food Service Equipment Manufacturer

Unit 2, Trevanah Road  
Troon Industrial Park  
LE4 9LS - Leicester

[uksales@sammic.com](mailto:uksales@sammic.com)  
Tel.: +44 0116 246 1900



Project

Date

Item

Qty

Approved

product sheet  
updated 01/10/2021