

Project: \_\_\_\_\_ Location: \_\_\_\_\_ Item #: \_\_\_\_\_ Quantity: \_\_\_\_\_

### Standard Features

- Kettle System-Seamless deep-drawn 304 kettle liner with an integrally formed radius lip, 304 stainless draw off tube and welds, 304 stainless 2" compression draw-off
- 304 stainless kettle jacket
- Kettle protection system- thermostat temperature control, 150° F - 260° F, pressure relief valve, air eliminator valve, pressure gauge, jacket-water fill, automatic low water cut off and indicator light, safety pilot control
- Full body insulation between kettle jacket and outer casing
- Electric ignition, 120V standard
- 304 stainless outer casing seam welded to radius lip
- 304 stainless, seam welded control console
- 304 stainless, one piece, domed cover, actuator-assisted on 40-100 gallon
- Perforated disc strainer, 1/4" holes
- Adjustable bullet feet

### Optional Features

- Single or dual faucet with bracket & 12" or 18" swing nozzle\*
- 60" flexible spray hose assembly (vinyl or stainless) for dual or single faucet\*
- Faucet bracket (ALFBST)
- Riser for table mounted fill faucet (ALRISER)
- Automatic water filling meter (ALACWS)
- Correctional Package\*
- Adjustable flanged feet (ALFF-200)
- 316 Liner for 40+ Gallon (AL316LNR)

\* Call AccuTemp for additional information

### Electrical Options

120V, 208V, 240V

### Short Spec

AccuTemp Edges Series gas powered, 2/3 jacketed, non-tilting floor kettle, low rim model ALLGB-100F. Seamless deep-drawn 304 kettle liner with integrally formed radius lip and 304 stainless steel kettle jacket. 2" compression draw-off valve that includes a perforated disc strainer (1/4" holes), pressure relief valve, air eliminator valve, pressure gauge, jacket-water fill valve, automatic low water cut off and indicator light. 304 stainless domed cover with spring assisted (40-100 gallon units). Seam welded control console with thermostat temperature control, 150°F to 260°F (65°C to 126°C). Adjustable bullet feet.

### Other Approvals

GAS-FIRED



### Accessories

- Care Kit (ALKCK-L)
  - Electric timer with buzzer (ALAT)
  - Gas quick disconnect 1/2"\*
  - Flexible gas hose 3/4" x 60" (ALTQDH)
  - Draw off drain hose (ALDIH)
  - Disc strainer; solid or perforated, 1/8" or 1/4"\*
  - Measuring strip (ALMS)
  - Lift-off or two piece hinged\*
  - One piece actuator-assisted lid, 15-30 gal. (ALACT-M)
  - Single basket 20-40 gal. (ALSBI-M)
  - Tri-basket insert (ALTBI-S)
  - Nylon bag insert with spreader ring (ALNBI)
  - 3" draw off valve optional
- \* Call AccuTemp for additional information



Model ALLGB-40F shown with included tangent draw off valve and lid

LOW-RIM™ MODEL ALLGB-100F DIMENSIONS										
Gal.	A	B	C*	D	E	F	J*	S*	V	W
100	44.0	22.5	27.5	35.1	23.9	55.6	91.5	28.2	14.6	24.0

\*Dimensions on these drawings are applicable only when using a 1.5" diameter draw-off valve. If a 2" or 3" diameter draw-off valve is required, contact AccuTemp for applicable dimensions.

Gal.	BTU RATING		Natural	Propane	Electrical
	Natural	Propane			
100	154,800	149,200	Supply Piping: 3/4" IPS Supply Pressure: 5-7" W.C. (nominal) Outlet Pressure Factory Setting: 3.5" W.C.	Supply Piping: 3/4" IPS Supply Pressure: 12-14" W.C. (nominal) Outlet Pressure Factory Setting: 10.0" W.C.	120 volt (standard) 208/240 volt (optional) 50/60 Hz 1 Phase 1 Amp

Revision 113

