

WE RAISE THE BAR. WE SET THE STANDARD.

Project Item Number Quantity

SL120LH/SL120LB

SL120LH / SL120LB SILVERLINE Spiral Mixers with Attached Lifter

Models:

> SL120LH: 265lbs (120Kg) Spiral Mixer

> SL120LB: 265lbs (120Kg) Spiral Mixer





Features:

- Stainless steel bowl, spiral dough hook, and shaft
- Separate bowl and agitator motors
- Has two speeds and reverse function
- Control board has separate timers for 1st and 2nd speed
- Mixer is equipped with built in lifter for lifting and discharge of mixed products
- Lifter can tilt machine to the right or left (must specify when ordering)
- Difference between H and B models is the height of the lifter (one for bench top and one for hoppers)
- Safety switches protect operator from injury if bowl lid is open
- Powerful belt drive provides low vibration, low noise, and economical maintenance for years of reliable service

Dough hook: 1st speed: 95rpm 2nd speed: 190rpm Bowl Speed: 15rpm

Warranty:

• One year, on-site parts and labor

Univex Corporation

Attached Lifter



ivex

Univex Corporation www.Univexcorp.com

3 Old Rockingham Rd Salem, NH 03079 United States of America TEL: (800)258-6358 INTL TEL: (603)893-6191 FAX: (800)356-5614 INTL FAX: (603)893-1249

LH-








SILVERLINE Spiral Mixer with Attached Lifter


SL120LH / SL120LB

SL120LH












SL120LB









Transmission: Heavy duty low noise, low vibration belt drive.

Bowl Guard: Swings open for full access to bowl. Guard must be closed for mixer operation.

Controls: Control panel with manual timers. Seperate timers for high and low speed. Security key for manual use. Bowl reverse direction switch. Up and down buttons.

Plug Info: Hard wire with shutoff

| Electrical Information (60Hz) | | | | | | | | | | | |
|-------------------------------|------------------|-------|---------------|-------------|---------------|--------------|-------------|-----------|-------------|------------|--|
| Model | Standard Voltage | Phase | Spiral hp(kW) | Bowl hp(kW) | Lifter hp(kW) | Total hp(kW) | Sprial Amps | Bowl Amps | Lifter Amps | Total Amps | |
| SL120LH | 220 | 3 | 8 (6) | 1 (.75) | 3 (2.2) | 12 (8.95) | 27.20 | 4.48 | 13.00 | 31.68 | |
| SL120LH Optional | 380 | 3 | 8 (6) | 1 (.75) | 3 (2.2) | 12 (8.95) | 13.5 | 2.24 | 6.5 | 15.9 | |
| SL120LB | 220 | 3 | 8 (6) | 1 (.75) | 3 (2.2) | 12 (8.95) | 27.20 | 4.48 | 13.00 | 31.68 | |
| SL120LB Optional | 380 | 3 | 8 (6) | 1 (.75) | 3 (2.2) | 12 (8.95) | 13.5 | 2.24 | 6.5 | 15.9 | |

| Shipping Information | | | | | | | | | |
|----------------------|----------------------|----------------------|---|--|--|--|--|--|--|
| Model | Net Weight | Shipping Weight | Overall Dimensions | | | | | | |
| SL120LH | 3,527 lbs. (1,600Kg) | 3,877 lbs. (1,759Kg) | 91" (231.1cm) H x 96" (243.8cm) W x 60" (152.4cm) D | | | | | | |
| SL120LB | 2,866 lbs. (1,300Kg) | 3,216 lbs. (1,459Kg) | 67" (170cm) H x 96" (243.8cm) W x 60" (152.4cm) D | | | | | | |



Univex Corporation www.Univexcorp.com

3 Old Rockingham Rd Salem, NH 03079 United States of America TEL: (800)258-6358
INTL TEL: (603)893-6191
FAX: (800)356-5614
INTL FAX: (603)893-1249