



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CUP-11S C CI 230V 1N 50Hz

19098005

23/01/2024

DENOMINATION:

Refrigerated cabinet - Concept Snack with 1 door, at 50Hz.

DESCRIPTION :

- Interior and exterior in high quality austenitic stainless steel.
 - 50 mm, 40 kg/m³ injected polyurethane insulation.
 - Removable and height adjustable plastic-covered steel shelves (17 Snacksize levels) for easy cleaning. Equipment: 3 shelves per large door.
 - Forced draught cooling system.
 - Copper piping and aluminium flaps evaporator.
 - Digital display for electronic and digital control of temperature and defrosting.
 - Opened door delay alarm.
 - Self-closing and stay open doors. When opened less than 90° they close by themselves. When opened more than 135° they stay open.
 - Built-in drainage to get rid of waste liquids inside the unit.
 - Embedded bottom and curved panels inside for easy cleaning and maintenance.
 - Height adjustable stainless steel legs.
 - Tested in climatic class 4.
 - Inner LED lights with power switch (in refrigerated display cabinets and now also in freezing units).
- Refrigerated cabinet
- Castors included
- UK plug included

POSSIBLE OPTIONS :

- Stainless Backing
- Legs instead of castors
- Door frame resistance
- Glass door
- Locks
- Opposite Opening
- Pedal
- Remote group

POSSIBLE ACCESSORIES :


- REFRIGERATION
- ACCESSORIES

SUPPLIED ACCESSORIES:

- 12034317 Grid made in Epoxi (560x542) 3

DIMENSIONS

X Width	693 mm	X Gross width	760 mm
Y Depth	726 mm	Y Gross depth	800 mm
Z Height	2067 mm	Z Gross height	2084 mm
Net Weight	114,0 kg	Gross Weight	120,0 kg
Net volume	1,040 m ³	Gross volume	1,300 m ³



ELECTRICITY TECHNICAL SPECIFICATIONS

Amperage (A)	0,81 A
Electric frequency	50Hz
Electric power	0,183 kW
Voltage	230V - 1N

GAS TECHNICAL SPECIFICATIONS

Gas type	R-600a
----------	--------

COLD TECHNICAL SPECIFICATIONS

Annual elec. consumption	548,00 kWh
Clasif. Energy efficiency	C
Climate class	4
Cooling gas load	92,000 g
Energy Efficiency Index	44,04 %
Gross internal volume	506 L
Model Type	Vertical cabinet
Power consumption 24h	1,50 kWh
Refrigeration net.vol	386 L
Refrigeration power	0,361 kW

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1+T-2A
--------------------------	----------

OTHERS

Condensation system	Vent.
Number of doors	1



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CUP-11S C CI 230V 1N 50Hz

19098005

23/01/2024

