



**SBB-24-48GSS**

**SBB-24-60GSS**

**SBB-24-72GSS**

Doors	2	2	3
Exterior Dimensions (L x D x H)	48 <sup>7</sup> / <sub>8</sub> x 24 <sup>3</sup> / <sub>8</sub> x 35 <sup>5</sup> / <sub>8</sub>	60 <sup>7</sup> / <sub>8</sub> x 24 <sup>3</sup> / <sub>8</sub> x 35 <sup>5</sup> / <sub>8</sub>	72 <sup>7</sup> / <sub>8</sub> x 24 <sup>3</sup> / <sub>8</sub> x 35 <sup>5</sup> / <sub>8</sub>
Capacity cu.ft.	11.8	15.8	19.6
HP	1/3	1/3	1/3
Voltage	115/60/1	115/60/1	115/60/1
Amps	6.4	6.4	7.4
Nema Config	5-15P	5-15P	5-15P
Crated/Uncrated Weight	231/216 lb	290/255 lb	352/310 lb

- Standard Stainless exterior
- Standard interior construction utilizes stainless steel walls, floor and ceiling
- Refrigeration system uses R134a Refrigerant which is CFC and HCFC-free for compliance with environmental safety concerns
- Oversized, factory balanced, refrigeration system holds 33°F to 38°F (0.5°C to 3.3°C)
- NSF-7 approved for packaged and bottled product
- LED lighting: Visibility of products, last longer and consume low energy
- Digital temperature control: Adjustable temperature set point and defrost frequency as well as error codes to diagnose service issues
- Easily accessible condenser coil for cleaning and easy service access
- Designed to accommodate a variety of beer kegs

\* Specifications subject to change without notice

