



PROJECT: \_\_\_\_\_

ITEM # \_\_\_\_\_ QTY: \_\_\_\_\_

MODEL # \_\_\_\_\_

AIA # \_\_\_\_\_ SIS # \_\_\_\_\_

## CHEF BASE FREEZER

### CBF48HC



### EXCLUSIVE WARRANTY

- ▶ 7 Year Parts, Labor and Compressor
- ▶ Exclusive 2 Year Warranty On Magnetic Door Gaskets
- ▶ Lifetime Warranty On Handles & Hinges (parts only)



### CABINET CONSTRUCTION

- Stainless Steel Exterior (galvanized back & bottom)
- Aluminum Interior
- Marine Top Standard
- 3" Heavy Duty Casters
- 10' Cord And Plug (see electrical data for details)

### REFRIGERATION

- Refrigeration System Uses R-290 Refrigerant To Comply With All Environmental Concerns
- Adaptive Defrost For Reduced Energy Consumption And More Consistent Product Temperatures
- Electric Defrost Heater With Hot Gas Condensate Evaporation
- Freezer Capable Of Maintaining Product Temperature Of -10°F

### FEATURES

- High Performance Refrigeration System With Electronic Control
- Top Weight Capacity 1000 lbs
- Heavy-Duty Drawer Slide Roller System
- 275 lbs Drawer Load Rating (per drawer)
- Heavy Duty, Fire-Proof Insulated, 16 Gauge Top
- No Heat Shield Required (must adhere to proper clearance per owners manual)
- Accommodates 6" Deep Full Size Food Service Pans (not included)
- Self-Closing Drawer Feature
- One Piece, Snap-In, Magnetic Drawer Gasket
- Compressor Available On Left Or Right, Specify At Time Of Unit Order



Please Verify Qualifying Units By Visiting:  
[www.energystar.gov/cfs](http://www.energystar.gov/cfs)

### OPTIONS & ACCESSORIES

- |                            |                              |                                                                                                         |
|----------------------------|------------------------------|---------------------------------------------------------------------------------------------------------|
| • Stainless Steel Back     | • Additional Pan Supports    | • Flat Top Overhang (any size up to 6" overhang on each side)                                           |
| • Stainless Steel Interior | • 6" Casters                 | • Remote Models* (6" legs only) (refrigerant must be specified at time of order, see note on back page) |
| • Drawer Locks             | • 6" Legs Or 6" Seismic Legs |                                                                                                         |

3779 Champion Blvd, Winston-Salem, NC 27105




ph: (888) 845-9800 | fax: (800) 253-5168

Sales@VictoryRefrigeration.com | VictoryRefrigeration.com


Rev. 5/27/25 Printed in U.S.A.

APPROVAL: \_\_\_\_\_ DATE: \_\_\_\_\_

CHEF BASE FREEZER



#### Drawer Configurations



We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM)

3 3/16" Bottom & 1" Rear clearance is required

| CHARACTERISTICS                   |                  | ELECTRICAL DATA                 |                    | SHIPPING DETAILS                                                                                           |         |
|-----------------------------------|------------------|---------------------------------|--------------------|------------------------------------------------------------------------------------------------------------|---------|
| Net Capacity (cubic ft.)          | 8.06             | Cabinet Voltage                 | 115/60/1           | Height                                                                                                     | 27"     |
| Width, Overall (in.)              | 48"              | Total Amperes                   | 5.0                | Width                                                                                                      | 58"     |
| Depth, Overall (with handle)      | 34 1/4"          | NEMA Plug (10' cord)            | 5-15P              | Depth                                                                                                      | 38"     |
| Height Overall (with casters)     | 24 3/8"          | REFRIGERATION DATA              |                    | Crated Weight                                                                                              | 375 lbs |
| Depth, Drawer Open 90°            | 57 1/4"          | Condensing Unit Size, HP        | 1/2                | *NOTE: Remote units are field wired and come with 6" legs. Refrigerant must be specified at time of order. |         |
| Drawer Openings (in.)             | 27 3/8" x 6 1/2" | Refrigerant*                    | R-290              |                                                                                                            |         |
| No. Of Drawers / Pans (full size) | 2 / 4            | Capacity (BTU/HR) (100°F/-20°F) | 1725               |                                                                                                            |         |
|                                   |                  | Heat Rejection (BTU/HR)         | 2588               |                                                                                                            |         |
|                                   |                  | Charge (lbs/grams/ounces)       | 0.287 / 130 / 4.59 |                                                                                                            |         |

3779 Champion Blvd, Winston-Salem, NC 27105 | ph: (888) 845-9800 | fax: (800) 253-5168

Sales@VictoryRefrigeration.com | VictoryRefrigeration.com

Rev. 5/27/25 Printed in U.S.A.