







SBB-24-48G	SBB-24-60G
0DD 27 700	

	SBB-24-48G	SBB-24-60G	SBB-24-72G
Doors	2	2	3
Exterior Dimensions (L x D x H)	48 % x 24 % x 35 %	60 % x 24 % x 35 %	72 % x 24 % x 35 <sup>5</sup> %
Capacity cu.ft.	11.8	15.8	19.6
НР	1/3	1/3	1/3
Voltage	115/60/1	115/60/1	115/60/1
Amps	6.4	6.4	7.4
Nema Config	5-15P	5-15P	5-15P
Crated/Uncrated Weight	260/216 lb	304/255 lb	354/310 lb

- Standard cabinet exterior construction includes attractive, wear resistant vinyl on steel in black finish
- Standard interior construction utilizes stainless steel walls, floor and ceiling
- Refrigeration system uses R134a Refrigerant which is CFC and HCFC-free for compliance with environmental safety concerns
- Oversized, factory balanced, refrigeration system holds 33°F to 38°F (0.5°C to 3.3°C)
- NSF-7 approved for packaged and bottled product
- LED lighting: Visibility of products, last longer and consume low energy
- Digital temperature control: Adjustable temperature set point and defrost frequency as well as error codes to diagnose service issues
- Easily accessible condenser coil for cleaning and easy service access
- Designed to accommodate a variety of beer kegs
- \* Specifications subject to change without notice



