

# Counter Top Induction Hobs



AT 25A



AT 25C



CT 35A



AT 50A



CT 70A

## KEY FEATURES

- Safe, Efficient and Fast
- Ideal to use near guests for theatre style, outdoor or front of house cookery
- Precise control – change temperature instantly and accurately (both Rotary and touch pad control panels available)
- Easy to clean both the hobs and pans
- Lower in time, cost and energy usage compared to gas, electric and halogen

## EXTRA SPEC DETAILS

- External Finish – Stainless Steel & Ceran Glass



Model	Dimensions (wxdxh) mm	Ceran Glass Dimensions mm	Electrical Consumption Watts	Power Supply	Control Panel	Settings	LED Display	Weight Kg
AT25A	328 x 422 x 100	273 x 273 (4mm thick)	2500 (13 amp plug)	230v 1 phase	Rotary	9 power levels, 5 temperatures	Power & temperature	7
AT25C	328 x 422 x 100	273 x 273 (4mm thick)	2500 (13 amp plug)	230v 1 phase	Touch Pad	9 power levels, 7 temperatures	Power & temperature	7
CT35A	385 x 520 x 177	300 x 300 (6mm thick)	3500	230v 1 phase 20 amp supply	Rotary	19 power levels, 20 temperatures	Power & temperature & timer	13
AT50A	385 x 520 x 197	300 x 300 (6mm thick)	5000	380/415v	Rotary 3 phase	19 power levels, 4 pre-set buttons	Power	15
CT70A	400 x 735 x 195	350 x 550 (6mm thick)	2 x 3500 (7 kW)	230v 1 phase 32 amp supply	Rotary	19 power levels, 4 pre-set buttons per hob	Power & temperature	26