



SBB-24-72GSS

- CABINET CONSTRUCTION**
Standard, cabinet exterior construction includes attractive, wear resistant vinyl on steel in black finish. Stainless exterior options available. Standard interior construction utilizes stainless steel walls, floor and ceiling.
- REFRIGERATION**
Refrigeration system uses R134a refrigerant, which is CFC and HCFC-free for compliance with environmental safety concerns.
- ELECTRICAL**
Units wired at factory and ready for connection to a 115/60/1 phase, 15 amp dedicated outlet.
- TEMPERATURE**
Oversized, factory balanced, refrigeration system holds 33°F to 38°F (0.5°C to 3.3°C)
- SANITATION**
NSF-7 approved for packaged and bottled product.


MODEL FEATURES:

- Standard LED light inside of the cabinet
- Easily accessible condenser coil for cleaning, and easy service access
- Tempered glass to avoid injury by broken glasses

Rough-In Data

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

Model	Doors	Cabinet Dimensions (inches / mm)			Capacity	HP	Voltage	Amps	NEMA Config.
		L	D	H					
SBB-24-72GSS	3	72 3/4 1848	24 3/8 620	35 5/8 905	19.6 cu.ft. 556L	1/3+	115V/60Hz 220V/50Hz	7.4	5-15P 



- Plug type varies by country.
- Height does not includes 3" casters.

SBB-24-72GSS Plan View

