

CRYSTAL MOBILE PROVER TECHNICAL DATASHEET

C1MP20 CRYSTAL MOBILE PROVER



C1MP20

Dimensions (mm)	External	Internal
Width	737	587
Depth	941	800
Height	2140	1503
Door Opening		1636

Capacity

Capacity (18x30" Trays)	19
-------------------------	----

KEY FEATURES

- Foodsafe stainless steel exterior and interior
- Self closing doors
- Precision injected, high density 75mm polyurethane insulation
- Heavy duty, non-marking swivel castors with brakes
- Barrel locked doors

OPTIONS

- Additional trayslides (18x30" - 2 slides)
- Stainless steel back
- Metric tray kit (600 x 400)
- 18 X 30" coated shelves



PRODUCT TECHNICAL DATA

Crystal Mobile Prover	C1MP20
Temperature (°C)	+38/+40
Power Supply	220V/240V 50Hz/1Ph
Fuse (Amps)	13
Fittings	
Trayslides	19
Electrical Data	
Running (Amps)	9.5

IMPORTANT NOTES:

Allow minimum of 500mm above cabinet for maintenance and ventilation.

All refrigeration equipment requires adequate ventilation for efficient and effective performance.

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration
Bryggen Road,
North Lynn Industrial Estate
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000
Spares: +44(0) 1553 817 017
E info@williams-refrigeration.co.uk
W www.williams-refrigeration.co.uk

