



# VACUUM PACKING MACHINE SU-604G 230-400/50/3N

Floorstanding unit. 40 m<sup>3</sup>/h. 413+656 mm.



1140813



## INCLUDES

- ✓ BUSCH pump.
- ✓ Sensor Controls.
- ✓ 25 programmable settings.
- ✓ Vacuum PLUS: up to 10 seconds of extra vacuum pull.
- ✓ Soft air function.
- ✓ Clear methacrylate lid.
- ✓ "PAUSE" function.
- ✓ Liquid detection system.
- ✓ Dry oil cycle.
- ✓ NSF Approved.
- ✓ Filling plate.

## ACCESSORIES

- Bag cutting kits
- Filling plates
- Liquid insert plates
- Vac-norm external vacuum kits
- Vac-norm containers
- Smooth bags for vacuum packing
- Thermal labels for CG2 / RB printer
- RB Desktop printer for SU vacuum packing machines \*
- Thermal transfer labels for RB printer

## SALES DESCRIPTION

Two sealing bars (413+656 mm.)  
40 m<sup>3</sup>/h Busch vacuum pump.  
Vacuum controlled by sensor.

- ✓ Powered by Busch.
- ✓ Vacuum controlled by sensor.
- ✓ Vacuum PLUS.
- ✓ LCD colour screen: all information at a glance.
- ✓ Backlit touch keyboard.
- ✓ Programmable: 25-programme memory. Blocking option.
- ✓ "Pause" button.
- ✓ Phased vacuum programme.
- ✓ Detection of the evaporation of liquids.
- ✓ Double seal.
- ✓ Cordless sealing bar.
- ✓ Progressive decompression.
- ✓ Vac-Norm ready with Automatic decompression.
- ✓ Stainless steel body and chamber.
- ✓ Damped transparent lid of high durability polycarbonate.
- ✓ Dry-oil programme for drying the pump.
- ✓ Working hours counter for oil changes.
- ✓ Safety system with protection against vacuum failure.
- ✓ NSF-listed.



[www.sammic.co.uk](http://www.sammic.co.uk)

Food Service Equipment Manufacturer

Unit 2, Trevanah Road  
Troon Industrial Park  
LE4 9LS - Leicester

[uksales@sammic.com](mailto:uksales@sammic.com)  
Tel.: +44 0116 246 1900



Project

Date

Item

Qty

Approved

FOOD PRESERVATION AND SOUS-VIDE  
VACUUM PACKING MACHINES - "SENSOR ULTRA" LINE

product sheet  
updated 11/01/2021



# VACUUM PACKING MACHINE SU-604G 230-400/50/3N

Floorstanding unit. 40 m<sup>3</sup>/h. 413+656 mm.



1140813

## SPECIFICATIONS

Pump capacity: 40 m<sup>3</sup>/h  
 Pump capacity (60 Hz): 48 m<sup>3</sup>/h  
 Bar length: 413 mm + 656 mm  
 Total loading: 1100 W  
 Vacuum pressure (maximum): 0.5 mbar  
 Electrical supply: 400 V-230 V / 50 Hz / 3N  
 ~ (5.9 A)

### Internal dimensions

- ✓ Width: 672 mm
- ✓ Depth: 481 mm
- ✓ Height: 200 mm

### External dimensions (WxDxH)


- ✓ Width: 740 mm
- ✓ Depth: 566 mm
- ✓ Height: 997 mm

Net weight: 145 Kg

Noise level (1m.): 75 dB(A)  
 Background noise: 32 dB(A)

### Crated dimensions

670 x 830 x 1200 mm  
 Gross weight: 173 Kg.



FOOD PRESERVATION AND SOUS-VIDE  
 VACUUM PACKING MACHINES - "SENSOR ULTRA" LINE

**www.sammic.co.uk**

Food Service Equipment Manufacturer

Unit 2, Trevanth Road  
 Troon Industrial Park  
 LE4 9LS - Leicester

uksales@sammic.com  
 Tel.: +44 0116 246 1900

Project	Date
Item	Qty
Approved	

product sheet  
 updated 11/01/2021