

MANUAL GAS BOILER 43 lt. WITH IRON BOTTOM (Extra EU)

Project:
Rev:
Zone:
Location:



CODICE
CR0989959

MODELLO
D74/10KBG

SERIE
DIAMANTE70



GENERAL CHARACTERISTICS

In addition to offering the widest choice of solutions and 2 mm thick and 70 cm deep tops, this series has all the power, robustness and functionality you need to work efficiently. Scotch Brite finish stainless steel outer shells and feet. Worktop height adjustable from 840 to 900 mm. Modularity of range: 200-400-600-800-1200 Wide range of accessories.

TECHNICAL SPECIFICATIONS

Multifunctional tilting braising pan, equipment for professional catering, suitable for cooking sauces, braises and cooking with oil. It guarantees high performance, exceptional firing uniformity. Water supply directly into the tank via solenoid valve (can be ordered as an accessory).
Cooking temperature controlled by thermostat with adjustment from 100 to 280°C.

IRON baking tray (available for non-EU markets) with 2 mm thickness.

Cooking temperature controlled by thermostat with adjustment from 100 to 280°C.

Heating by chrome-plated steel burner.

Safety valve with thermocouple, electric ignition.

Robust, double-walled, self-balancing lids made of stainless steel to reduce heat loss.

Large-radius tilting tank.

Equipment certified for low voltage directive 2014/35/EU according to the international CB scheme.

Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.

MANUAL GAS BOILER 43 lt. WITH IRON BOTTOM (Extra EU)

Project:
Rev:
Zone:
Location:



CODICE
CR0989959

MODELLO
D74/10KBG

SERIE
DIAMANTE70

Technical Information

SPECIFICATION	DATA
MATERIAL	CR0989959
DEFINITION	D74/10 KBG BRAZIER GAS M80 FE
COMMERCIAL LINE	DIAMANTE
SUPPLY	GAS
DIM. WIDTH	800 mm
DIM. PRODUCTIVITY	730 mm
DIM. HEIGHT	870 mm
NET WEIGHT	135,000 Kg
VOLUME (net)	0,508
PACKAGE LENGTH	840,000 mm
PACKAGE WIDTH	850,000 mm
PACKAGING HEIGHT	1050,000 mm
PACKAGE VOLUME	0,800 m3
GROSS PACKING WEIGHT	146,000 Kg
STANDARD POWER SUPPLY	220-240V 1N
FREQUENCY	50 Hz
ELECTRICAL POWER	0.12 kW
GAS POWER	14,00
GAS POWER (G25.3/25mbar)	13,00
CERTIFIED MODEL	D74/10 KBG

MANUAL GAS BOILER 43 lt. WITH IRON BOTTOM (Extra EU)

Project:
Rev:
Zone:
Location:




CODICE
CR0989959

MODELLO
D74/10KBG


SERIE
DIAMANTE70

SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION - ESQUEMA DE INSTALACION - INSTALLATIESCHEMA - IINSTALLATIONSRIJNINGAR

MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm
MESURES EN cm - MEDIDAS EN cm - MATEN IN cm



(D) 74/10 KBG ...



Legenda - Legende - Key - Légende - Leyenda - Legenda

- G** Attacco arrivo gas - Gasanschluss - Gas connection
Arrivée gaz - Union de gas - Gasaansluiting
EN 10226-1 R 1/2; EN ISO 228-1 G 1/2 (DK)
- S** Scarico vasca - Wannenabflussrohr - Pan outlet
Vidange du bac - Descarga cuba - Water toevoer

MANUAL GAS BOILER 43 lt. WITH IRON BOTTOM (Extra EU)

Project:
Rev:
Zone:
Location:



CODICE
CR0989959

MODELLO
D74/10KBG

SERIE
DIAMANTE70

Product's PLUS



Self-balancing lids.



Large-radius tilting tank.



Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.

MANUAL GAS BOILER 43 lt. WITH IRON BOTTOM (Extra EU)

Project:
Rev:
Zone:
Location:



CODICE
CR0989959

MODELLO
D74/10KBG

SERIE
DIAMANTE70

ACCESSORIES

CODE	MODELLO	DESCRIZIONE
CR0592799	ZF8	
CR0592830	ZG	
MA97432000	R	
MA97433000	RI	
CR0592869	PZM	
CR0593580	9PT	
CR0592879	KPA	
CMF0708	CMF0708	
CR0599649	7ZL	