

| APPLICATION: | | PRODUCT NAME: |
|--------------|----------|--|
| | | POT FILLER SINGLE WALL MOUNT WITH DOUBLE JOINT SPOUT |
| JOB NAME: | | SPECIAL CONFIGURATION CHECK BASE MODEL AND OPTIONS |
| QUANTITY: | ITEM NO. | MODEL: |
| 11" | | ☐ 4730 W/ 18" DJ SWING SPOUT |
| | | ☐ 4731 W/ 24" DJ SWING SPOUT |
| | | OPTIONS OR MODIFICATIONS: |
| | | SUPPLY LINES (24" OR 36") CIRCLE LENGTH |



| MODEL | DIM "A" | DIM "B" |
|-------|------------------|------------------|
| 4730 | 7" [177.8mm] | 18" [457.2mm] |
| 4731 | 13" [330.2mm] | 24" [609.6mm] |

ROUGH-IN:



FEATURES

☐ OTHER

□ NIPPLE□ ELBOW

CONTROL VALVE

- * SINGLE WALL MOUNT
- * SWIVELING SEAT DISK

☐ VANDAL RESISTANT KIT

- * FAUCET STEM RIGHT HAND
- * SPOUT STEM RIGHT HAND
- * STAINLESS STEEL SEAT
- * STAINLESS STEEL SEAT SCREW
- * STAINLESS STEEL HANDLE SCREW

☐ HANDLES (CROSS OR WRIST) CIRCLE STYLE

* HOT & COLD INDEX BUTTONS

SYSTEM LIMITS

- * TEMP: 40°F MIN. TO 140°F MAX.
- * PRESSURE: 200 PSI MAX. STATIC
- * 5.0 GPM AT 80 PSI

SHIPPING WEIGHT

* 4.0 LBS

FISHER MANUFACTURING COMPANY