

Specification/Data sheet

Booster transformer, 6-full, 10-full iCombi gas models



Article number: 87.00.740US

Description

The Booster transformer allows installation of an iCombi Pro or Classic 6-full or 10 full gas models on 120 V receptacles. The Booster is pre-wired for plug and play installation between the 120V receptacle and the iCombi. The iCombi must be set to 240V by trained technician at time of installation / commissioning.

Features

- Encapsulated transformer comes with 5' cable with NEMA 5-15 P and 3' cable with NEMA 6-15 R
- Bracket included for mounting to wall. Does not include hardware bolts to secure.
- Produces 240V power for 6-full size and 10 full size gas models.
- 1.5kVA Single Phase.
- One Booster per iCombi required.

Technical specifications

- Frequency Rating: 60 Hz
- Output voltage: 240V
- Max Temperature Rise: 115°C
- UL Insulation Class: 180°C
- IP Rating: IP14
- NEMA Enclosure Rating: 3R
- Dimensions: 10.3 in (H) x 5.3 in (D) x 5.5 in (W)
- Weight: 30 lb
- 20A breaker

Material

- 5' cable 90°C SOOW with NEMA 5-15 P (plug)
- 3' cable 90°C SOOW with NEMA 6-15 R (receptacle)
- Metal bracket for mounting Booster on wall/utility pole. (does not include mounting bolts)



Intended use

- This product is intended for professional use, such as in restaurant kitchens or catering operations for schools, hospitals, or delis. Any other use runs counter to its intended purpose and could be dangerous. RATIONAL AG assumes no liability for the consequences of improper use.



Specification/Datasheet

Booster transformer model 6-full, 10-full iCombi Gas Models



NOTES:

1. DIMENSIONS CAN BE CHANGED BY MANUFACTURER WITHOUT NOTICE.
2. DIMENSIONS DO NOT IMPLY TOLERANCE.

Units: inches