

FRY TOP S Electric M80 Chrome Plate - 1/3 Striped - On thermostat compartment

Project:
Rev:
Zone:
Location:



CODICE
CR1652399

MODELLO
D94/10SFTEC1/3R

SERIE
DIAMANTE90



GENERAL CHARACTERISTICS

In addition to offering the maximum choice of solutions and 2 mm thick and 90 cm deep tops, this series has all the power, robustness and functionality you need to work efficiently. External coatings and feet in stainless steel with Scotch Brite finish. Working table height adjustable from 840 to 900 mm. Range modularity: 200-400-600-800-1200. Wide range of accessories.

TECHNICAL SPECIFICATIONS

15 mm thick cooking plate totally independent of the hob .
Large floodable channel around the perimeter of the hotplate for collecting cooking residues, sloping towards the front for draining liquids into the large drawer.
Large grease collection drawer.
Uniform baking temperature over the entire plate.
Optimising heat in the cooking area and increasing the comfort of operators in the kitchen.
Plate not welded to the machine bed with optimisation of structural points under thermal stress
Stainless steel overflow plug, supplied as an accessory, for channel flooding management
Non-welded plate for fast maintenance and replacement in the utility
New version with identical cooking surface area and reduced energy output.
An increase in output per cm² allows a reduction in consumption of up to 15% compared to conventional versions

Floodable gutter for collecting cooking residues around the perimeter of the cooking plate easier cleaning and better retention of moisture in cooking food

Capacious grease collection drawer with capacity for the entire volume of the perimeter channel

Grooved plate design ensures cleanliness right to the end of the plate

Non-welded plate for fast maintenance and replacement in the utility

Plate not welded to the machine bed with optimisation of structural points under thermal stress

Thermal cutting that facilitates the user and adjacent machinery.

Uniform cooking temperature across the entire plate. Optimising heat in the cooking area and increasing operator comfort in the kitchen.

Water dispenser kit available as an accessory

FRY TOP S Electric M80 Chrome Plate - 1/3 Striped - On thermostat compartment

Project:
Rev:
Zone:
Location:



CODICE
CR1652399

MODELLO
D94/10SFTEC1/3R

SERIE
DIAMANTE90

Technical Information

SPECIFICATION	DATA
MATERIAL	CR1652399
DEFINITION	D94/10SFTEC1/3R FTE 1/3RC M80 A/G
COMMERCIAL LINE	DIAMANTE
SUPPLY	ELECTRICS
DIM. WIDTH	800 mm
DIM. PRODUCTIVITY	900 mm
DIM. HEIGHT	870 mm
NET WEIGHT	113,000 Kg
VOLUME (net)	0,626
PACKAGE LENGTH	840,000 mm
PACKAGE WIDTH	850 mm
PACKAGING HEIGHT	1170,000 mm
PACKAGE VOLUME	0,836 m3
GROSS PACKING WEIGHT	128,000 Kg
STANDARD POWER SUPPLY	380-415V 3N
FREQUENCY	50-60 Hz
ELECTRICAL POWER	15,000 kW
IP GRADE	IPX5
CERTIFIED MODEL	D94/10SFTEC1/3R

FRY TOP S Electric M80 Chrome Plate - 1/3 Striped - On thermostat compartment


Project:
Rev:
Zone:
Location:

CODICE
CR1652399

MODELLO
D94/10SFTEC1/3R

SERIE
DIAMANTE90

MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm- MESURES EN cm
MEDIDAS EN cm - MATEN IN cm - DIMENSIONES EN cm



Legenda - Legende - Key - Légende - Leyenda - Legenda - Legenda

E Pressacavo entrata linea elettrica - Stopfbuchse - Electric cable stress relief - Presse étoupe de câble él - Pisacable - Elektrische kabelwartel - Entrada cabo eléctrico	G Arrivo gas - Gasanschluss - Gas connection - Arrivée gaz - Union de gas - Gasaansluiting - Ligação gás
S Attacco scarico acqua - Wasserablauf - Water outlet - Vidange de l'eau - Desaguadero - Wateraftapaansluiting - Junção descarga água	H20 Arrivo acqua - Wasseranschluss - Water inlet - Arrivée eau - Union de agua - Wateraansluiting - Junção alimentação água
S1 Scarico vasca - Wannababflussrohr - Pan outlet - Vidange du bac - Descarga cuba - Water toevoer - Descarga da cuba	A1 Calda - Heiss - Warm - Chaude - Caliente - Warm - Morno
S2 Valvola di depressione - Anti-depression valve - Unterdruck ventil - Soupape de dépression - Válvula de depresión - Onderdrukklep - Válvula de depressão	A2 Fredda - Kalt - Cold - Froid - Fria - Koude - Frio
S3 Scarico acqua intercapedine - Wasserablauf Zwischenraum - Jacket water drain Evacuation eau double envelope - Descarga de agua intersticios - Afvoer water tussenruimte - Descarga de água na marmita com Sistema de aquecimento indirecto	L Rubinetto di livello - Level tap - Wasserhahn - Robinet de niveau - Grifo de nivel - Niveaakraan - Torneira de nivel
S4 Scarico - Abflussrohr - Drain - Tuyau d'évacuation - Tubo de drenaje - Aftapbuis - Tubulação de dreno	

FRY TOP S Electric M80 Chrome Plate - 1/3 Striped - On thermostat compartment

Project:
Rev:
Zone:
Location:



CODICE
CR1652399

MODELLO
D94/10SFTEC1/3R

SERIE
DIAMANTE90

Product's PLUS




Plate not welded to the machine bed with optimisation of structural points under thermal stress




Thermal cutting that facilitates the user and adjacent machinery.



Capacious grease collection drawer with capacity for the entire volume of the perimeter channel



Uniform cooking temperature across the entire plate. Optimising heat in the cooking area and increasing operator comfort in the kitchen.



Grooved plate design ensures cleanliness right to the end of the plate



Water dispenser kit available as an accessory



Non-welded plate for fast maintenance and replacement in the utility

FRY TOP S Electric M80 Chrome Plate - 1/3 Striped - On thermostat compartment

Project:
Rev:
Zone:
Location:



CODICE
CR1652399

MODELLO
D94/10SFTEC1/3R

SERIE
DIAMANTE90



Water dispenser kit available as an accessory

FRY TOP S Electric M80 Chrome Plate - 1/3 Striped - On thermostat compartment

Project:
Rev:
Zone:
Location:



CODICE
CR1652399

MODELLO
D94/10SFTEC1/3R

SERIE
DIAMANTE90

ACCESSORIES

CODE	MODELLO	DESCRIZIONE
CR1354989	PRPC	
CR1354999	PKLR	
CR1356399	RPR	Striped chrome plate scraper
CR1658629	D97CPFT68	Fry top cleaning drawer M60 - M80
CR1658609	97TFT	
CR1658689	D9AFT8	
CR1659159	Q94GKSCFT	
CR1658839	Q794CAFT	